

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 204700

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only, T32-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8601)

-----  
Intersect S. bdy. of Tp. 128 lks. W. of cor. of secs. 5, 6, 31 and 32, which is a quartz stone 8 x 10 ins., 3" above ground, marked and witnessed as described by the surveyor general. I destroy the marks referring to secs. 31 and 32, and at the point of intersection I set a dogwood post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 31 and 32, marked T32S R5W on N.; S32 on E.; and S31 on W. faces with 5 grooves on E. and 1 groove on W. faces, from which  
A Fir 36" dia. bears N.43°E., 57 lks. mkd T32S R5W S32 BT  
A Laurel 10" dia., bears N.38°W., 32 lks. marked T32S R5W S31 BT.

George J. Wenderoth, - For: Geo. Newman - 1953 - C.S. 49/112

-----  
Found C.C. sec. 32  
10" Madrona, N.38°W., 21.1 ft.  
36" Fir N.43°E., 37.6 ft., stump scribed  
Drive 1" Iron pipe for corner.  
Mark - 5" Fir N.36°45'W., 15.0 ft.  
6" Fir N.39°30'E., 29.5 ft.

Douglas County Surveyors Office - James Bryon, Deputy - Milo Godfrey, S.A. Bilow, crew - For: C & D Lumber Co. Aug. 1958 -C.S File 49/112 and M 12-51

-----  
Found - 1" Iron pipe and BTs as recorded by Wenderoth.  
One of Theil's BTs, 10" Laurel N.38°W., 21.1 ft., has open face, good scribing "BT"  
Set brass cap alongside 1" I.P. mkd: County Surveyors Office  
T 32 S R 5 W  
S31|S32  
S 5  
1958  
I destroy all evidence of standard corner and BTs:  $\frac{31|32}{6|5}$   
I reset old corner stone alongside brass cap.  
New BT - 5" W.Fir S.65°W., 11.6 ft. scribed "CC S31 - 32 CSBT"

Cor. Fd. OK, DCSO, Aug. 1967 C.S. File 53/52-16

Fd ok on BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20353-4)

cont.

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 204700

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found OK by M. Hull, Feb. 27, 2004 - M144-18

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21680-1)

-----  
The closing cor. of secs. 31 & 32, on the S. bdy. of the Tp. monumented with an iron post, 1½" dia. firmly set, projecting 12" above the ground, with brass cap (properly) mkd from which the remains of original bearing trees

A sawed decayed fir stump, 36" dia., bears N.43°E., 37.6 ft., no marks visible.

A root hole with madrone alongside, 14" dia., bears N.38°W., 21.1 ft., no marks visible.

and a bearing tree mkd. by Wenderoth, in 1953, reported by Nickerson in 1989-92 as being marked by the Douglas County Surveyor's Office

A fir, 17" dia., bears N.39½°E., 29.7 ft., with a healed blaze.

and a bearing tree mkd. by Wenderoth, in 1953

A fir, 14" dia., bears N.39½°W., 15.0 ft., with a healed blaze.

and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1958, reported by Nickerson in 1989-92

A fir snag, 8" dia., bears S.65°W., 11.6 ft., with a healed blaze.

A quartz stone 6x8" projecting 4" above the ground, and an iron pipe, 1½" dia., projecting 11" above the ground, are both found alongside the iron post.

(NAD 1983 (CORS 96))

Latitude: 42°44'22.14"N. Longitude: 123°19'39.23"W.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24117)

-----  
The closing cor. of secs. 31 & 32, T32S R5W reported by Rambo & Simon in 2006-07, bears N.89°21'01"W., 83.67 ft; monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd from which the remains of BTs reported by Rambo and Simon

A fir, 20" dia., bears N.39½°E., 29.7 ft., with a healed blaze.

A rotted fir stump, 36" dia., bears N.43°E., 37.6 ft., no marks visible. (Original)

A fir, 16" dia., bears N.39½°W., 15.0 ft., with a healed blaze.

Continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 204700

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A quartz stone, 6x8", projecting 4" above the ground, and an iron pipe, 1 1/2" dia., projecting 11" above the ground, are both found alongside the iron post.