

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 306700

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 32 and 33 only, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCS0 records Vol. 20 Page(s) 8599)

At point of intersection, set a dogwood post, 3 ft. long, 4" sq., 24" in the ground for closing corner of secs. 32 and 33, marked C C T32S R5W on N.; S33 on E.; and S32 on W. faces; with 4 grooves on E., and 2 grooves on W. faces, from which
A Fir 72" dia., bears N.61°E., 33 lks. marked T32S R5W S33 BT.
A Maple 10" dia., bears N.9°W., 16 lks. marked T32S R5W S32 BT.

George J. Wenderoth - For: Geo. Newman - 1953 - C.S. File 49/112

Find corner to secs. 32 and 33, T32S R5W. Find:
84" Fir N.61°E., 21.7 ft. No scribe shows.
Old stake marked C.C. 32 & 33.
Drive 3/4" iron rod for corner. Mark
7" Maple N.24°15'W., 42.0 ft.

Survey by Norman Price - For: Dollar and Patterson Lumber Co. July 1953 - C.S. File 41/184

The closing cor. of secs. 32 and 33, T32S R5W, monumented with an iron bolt, 1" dia., 6" above ground, firmly set, from which
A D.Fir 60" dia., bears N.60°E., 35 lks. dist., mkd. CC 33 CS BT.
A Maple 8" dia., bears N.26°W., 63 lks. dist., mkd. CC 32 CS BT.
Find no evidence of the Ives and Hyde cor. of secs. 4, 5, 32 and 33.

Douglas Co. Surveyors Office - John M. Powell, Joe Brady, crew - August 1967 - C.S. File 53/52-49

Found - 60" Fir stump N.59°E., 22.1 ft. mkd. CC T32S R5W S33 CS BT.
1" Axle at corner set by Norman Price, 1953 (C.S. File 41/184)
New BTs -10" D.Fir N.24°E., 20.6 ft. mkd. CC T32S R5W S33 CS BT.
12" D.Fir N.1°W., 17.2 ft. mkd. CC T32S R5W S32 CS BT.

continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 306700

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 32 and 33 only, T32-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/6/2000 - C.S. File 66/16-18

CONDITION REPORT

Found - 3/4" axle protruding 4" above ground. 1953
72" now 48" dia., rotted 3 ft. high D.Fir stump no
scribing or blazes remaining, bears N.61°E., 24.8
ft. (Orig. rec. N.61°E., 21.8 ft. probable face
measurement) OBT
7" now 16" dia., Maple with a fully healed single
blaze bears N.26°W., 42.0 ft. 1953
10" now 22" dia., D.Fir with a fully healed single
blaze, bears N.24°E., 20.6 ft. 1967
12" now 26" dia., D.Fir with a fully healed single
blaze bears N.1°W., 17.2 ft. 1967

Found OK by M. Hull, Feb. 2004 - M144-18
Fd. OK by D. Edwards, 7/2010 - C.S. File 65/69-34

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,
under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCS0
records Vol. 59 Page(s) 24114-5)

The closing cor. of secs. 32 and 33, T32S R5W perpetuated by
Wenderoth, in 1953; subsequently perpetuated by the Douglas
County Surveyor's Office in 1967, bears North, 4.43 ft.;
monumented with an axle, 1" dia., firmly set, projecting 5"
above the ground, from which the remains of an original BT

A rotted fir stump, size indeterminate, bears N.61°E.,
21.8 ft., no marks visible.

and a bearing tree mkd. by Wenderoth

A maple, 18" dia., bears N.26¼°W., 42.3 ft., with a healed
blaze.

and BTs mkd. by the Douglas County Surveyor's Office

A fir, 30" dia., bears N.23½°E., 20.8 ft., with a healed
blaze.

A fir, 32" dia., bears N.0¾°W., 17.2 ft., with a healed
blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, directly over the axle, with brass cap mkd.

CC
T 32 S R 5 W
S 32 | S 33
S 4
T 33 S R 5 W
2021