

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 308700

PRIMARY CORNER DESCRIPTION A.P. #2 - No. Bdy. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 2- Page(s) 8549)

Set post cor. of secs. 32, 33, 4 and 5, from which
An Alder 10" dia., bears S.52°E., 41 lks.
An Alder 7" dia., bears S.53°W., 31 lks.
An Alder 10" dia., bears N.62°W., 8 lks.
An Alder 8" dia., bears N.82°E., 23 lks.

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8988)

Intersect Tp. cor. determined by bearing trees as post was missing.
Reestablished Tp. cor. to secs. 32 and 33 T32S R5W by setting a basaltic stone 12x10x5 ins., 8" in the ground marked with 4 notches on the E. and 2 notches on the W. edges, from which
An Alder 8" dia., bears N.82°E., 23 lks. dist., mkd. T32S R5W S4 BT.
An Alder 10" dia., bears N.62°W., 8 lks. dist., mkd. T32S R5W S32 BT.
The NE and SW trees were missing, burnt up. Therefore I established a NE tree which is an
Alder 7" dia., bears N.45°30'E., 24 lks. dist. mkd. T32S R5W S33 BT.

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8599)

Intersect S. bdy. of the Tp., 142 lks. W. of cor. to secs. 32, 33, 4 and 5, which is a granite stone 10x12x3 ins. above ground, marked as described the surveyor general, from which
An Alder 8" dia., bears N.82°E., 23 lks. mkd. T32S R5W S33 BT. (Old BT)
An Alder 10" dia., bears S.6°E., 38 lks. mkd. T33S R5W S4 BT. (New BT)
A Fir 50" dia., bears S.51°W., 72 lks. mkd. T33S R5W S5 BT. (New BT)
An Alder 10" dia., bears N.62°W., 8 lks. mkd. T32S R5W S32 BT. (Old BT)
I destroyed all marks, referring to secs. 32 and 33

(Cont. Next Page)

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 308700

PRIMARY CORNER DESCRIPTION A.P. #2, No. Bdy. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM remonumentation of corners by Lynn Roseberry, Cadastral surveyor, under Group #'s 936 and 1000, surveyed July 1977/April 1980 (DCSO records Vol. 42 Page(s) 16643)

The Ives and Hyde standard cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., determined at record bearing and distance from the remains of a bearing tree mkd. by Thiel:

A Fir snag 80" dia., bears S.51°W., 72 lks. dist., with scribe marks T33S R5W S5 B visible on opened blaze.

This corner now becomes angle point No. 2 of secs. 4 and 33. At the corner point

Set an iron post 28" long, 2½" dia., 20" in the ground, in a mound of stone, 3 ft. base, to top, with brass cap marked:

AP 2
T 32 S R 5 W
S 33
S 4
T 33 S
1980

from which new bearing trees

A W.Fir 14" dia., bears N.25¼°W., 27 lks. dist., mkd. AP2 S33 BT.

A Hemlock 14" dia., bears S.11½°W., 100½ lks. dist., mkd. AP2 S4 BT.

Corner is located 20 lks. East of Woodford Creek, 5 lks. wide, course N.

Found OK by M. Hull, Feb. 2004 - M144-18

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24114) (Added 9/10/2024)

Angle Point No. 2 bet. secs. 4 and 33, reported by Roseberry in 1977-80, monumented with an iron post, 2½" dia., firmly set, with top 6" below the surface of the ground, with brass cap (properly mkd) mkd.

from which the remains of BTs reported by Roseberry

A hemlock, 29" dia., bears S.11½°W., 66.3 ft., with a healed blaze.

A rotted fir snag, size indeterminate, bears S.51°W., 47.5 ft., with scribe marks 33S R5W visible on open blaze. (Original)

and a new bearing tree

A fir, 9" dia., bears N.34¼°W., 16.6 ft., mkd. AP2 S33 BT.

Continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 308700

PRIMARY CORNER DESCRIPTION A.P. #2 - No. Bdy. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Each new BT has a 2½"x¼"magnetic nail (Mag Nail) driven at the base on right side center and each monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

Gregg Neitsch - For: John Hancock Life Insurance Co - 12/2022
- M181-58

Found - 1980 BLM brass cap
62" dia., D.Fir stump, 15' height, visible scribing,
S.55°45'W., 50.0'
10" dia., W.Fir, visible scribing, N.33°55'W., 16.8'
(Rec. N.25½°W., 27 lks)