

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Edward F Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol 21 Pg 8980)  
-----  
A stone 2 ft x 2ft x 2 ft which I marked ¼ on W side for ¼ sec. Cor. With a cross (X) at exact corner point from which:  
A Live Oak, 5" dia., bears N.15°30'W. 105 lks. mkd: ¼ S BT  
A Live Oak, 5" dia., bears S.32°W., 83 lks., mkd: ¼ S BT.  
No trees east of line.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24133) Added 9/11/2024  
-----  
Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 8" in the ground, to bedrock, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.  
T 33 S R 5 W  
¼  
S 4 | S 3  
2021  
from which  
A live oak, 6" dia., bears N.19¼°E., 30.6 ft., mkd. X at breast height and BT at the base.  
A live oak, 7" dia., bears S.33¾°W., 30.6 ft. mkd. ¼ S4 BT

Gregg Neitsch - For: John Hancock Life Insurance Co - 12/2022 - M181-58  
-----  
Found - 2021 BLM BC/IP (as of 1/5/2023 not filed)  
8" dia., Live Oak, visible scribe, N.19°15'E., 30.6' - field  
8" dia., Live Oak, visible scribe, S.33°45'W., 30.6' - field.