

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 400653

PRIMARY CORNER DESCRIPTION Line tree, secs 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Edward F Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCS0 records Vol 21 Pg 8980)

North 2'W between secs 3 & 4 - 13 chains north of 1/4 corner. A fir, 60" dia., line tree marked with 2 notches on N and S sides.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCS0 records Vol. 59 Page(s) 24133) Added 9/11/2024

An original line tree, a fir, 60" dia., mkd. with 2 notches on the N. and S. sides. This now becomes an angle point; from which new reference monuments
An iron rod, 30" long, 5/8" dia., set 28" in the ground, bears S.80°15'49"E., 16.10 ft., with aluminum cap mkd. RM AP S3 16.10 FT TO COR 2021 and an arrow pointing to the cor.
An iron rod, 30" long, 5/8" dia., set 28" in the ground, bears S.19°17'49"W., 16.10 ft., with aluminum cap mkd. RM AP S4 16.10 FT TO COR 2021 and an arrow pointing to the cor.

Gregg Neitsch - For: John Hancock Life Insurance Co - 12/2022 - M181-58

Found - 60" dia., D.Fir, GL0 Line tree
RM, a 5/8" dia., with 2" dia., Alum. cap set in 2021 BLM resurvey (not filed as of 1/5/2023) S.80°15'49"E., 16.10' - field
RM, a 5/8" dia., with 2" dia., Alum. cap set in 2021 BLM resurvey (not filed as of 1/5/2023) S.19°17'49"W., 16.10' - field.