

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO recs Vol 21 Pg 8966)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10 and 11 marked T33S S2 on NE.; R5W S11 on SE.; S10 on SW.; and S3 on NW. faces, with 5 notches on the S. and 2 notches on E. edges, from which

A Fir 18" dia. bears N.36°E. 108 lks marked T33S R5W S2 BT
A Fir 40" dia. bears S.82°E. 61 lks marked T33S R5W S11 BT
A Fir 10" dia. bears S.21°30'W. 29 lks mkd T33S R5W S10 BT
A Matherone 14" dia bears N.54°W. 43 lks mkd T33S R5W S3 BT

GLO resurvey by Hans W. Thielsen, under Group #390, Surveyed, Oct. 1957 - (DCSO records Vol. 33 Page(s) 13919-20)

The sec. cor., determined at record distance from each of the original bearing trees

A Fir snag 20" dia., bears N.37½°E., 108 lks. dist., plainly blazed and healed. (Rec. bearing N.36°E.)
A Fir 44" dia., bears N.82°E., 61 lks. dist., plainly blazed and healed. (Rec. bearing, S.82°E)
A Fir 14" dia., bears S.20°W., 29 lks. dist., plainly blazed and healed. (Rec. bearing, S.21½°W.)
A Madrona 15" dia., bears N.53°W., 43 lks. dist., with no marks visible on face of decayed blaze. (Rec. N.54°W.)

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 33 S R 5 W
<u> S 3 S 2 </u>
S 10 S 11
1957

from which new bearing trees

A Fir 7" dia., bears S.57°E., 45 lks. dist., marked T33S R5W S11 BT.
A Cedar 5" dia., bears N.72°W., 42 lks. dist., marked T33S R5W S3 BT.

Douglas Co. Surveyors Office - John M. Powell, and Joe Brady, crew - Aug/Sept. 1967 - C.S. File 53/52-24

Found - 1957 GLO brass cap, properly marked.
Orig. 18" D.Fir now 22" snag, N.36°E., 71.3 ft. shows good face.
Orig. 40" D.Fir now 48" stump, S.82°E., 39.6 ft. opened and shows scribe of "S".

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec cor for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Orig. 10" now 18" stump, S.21½°W., 19.1 ft. shows good face.
Orig. 14" now 18" Laurel N.54°W., 28.4 ft. shows good face.
Rescribed BT:
18" Laurel N.54°W., 28.4 ft. mkd. T33S R5W S3 CS BT.
New BTs -6" W.Fir N.5°E., 39.1 ft. mkd. T33S R5W S2 CS BT.
6" Cedar S.23°E., 38.0 ft. mkd. T33S R5W S11 CS BT.
6" D.Fir S.41°W., 33.6 ft. mkd. T33S R5W S10 CS BT.

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1355, survey Dec. 1986/June 1992 - (DCSO records C.S. File 64/76-5)

The Cor. of secs. 2, 3, 10, & 11 monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground with (properly marked) brass cap, from which the remains of the OBTs:
A Fir snag, 20" dia., bears N.37½°E., 108 lks., with healed blaze.
A Fir stump, 45" dia., bears N.82°E., 61 lks., with healed blaze.
A Fir stump, 19" dia., bears S.20°W., 29 lks., with healed blaze.
and the remains of BTs mkd. by Thielsen
A root hole, bears S.57°E., 45 lks., alongside of which is lying the decayed remains of a fir, 9" dia., with healed blaze.
A root hole, bears N.72°W., 42 lks., alongside of which is lying a cedar, 10" dia., with scribe marks T33S R5W S3 BT visible on open blaze.
and the remains of BTs mkd. by DCSO in 1967
A Fir, 13" dia., bears N.7 3/4°E., 59 lks., with healed double blaze.
A sawed Cedar stump, 14" dia., bears S.22½°E., 57 lks., alongside of which is lying a Cedar, 14" dia., with healed blaze.
A Fir, 13" dia. bears S.42°W., 50½ lks. with healed blaze.
and a new BT
A Fir, 12" dia. bears S.59°E. 64 lks. mkd: T33S R5W S11 BT

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 6/2015 - C.S. File 65/89-8

Found - GLO brass cap (properly mkd).
20" Fir N.7¾°E., 38.9 ft. good scar.

23" Fir S.59°E., 42.2 ft. good scar. cont. next pg
TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

	14" Rotted cedar stump, S.22°E., 37.6 ft.
	20" Fir S.42°W., 33.3 ft. good scar.
New -	A 7" Fir N.67°W., 9.9 ft. scribed T33S R5W S3 BT.
Note -	Hand held Lat: N 42°43.479' & Long: W 123°16.161'
	Compass decl. 15½°E.