

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO recs Vol. 21 Pg 8968)</p> <p>-----</p> <p>Set a slate stone 18 x 12 x 6 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face from which</p> <p style="padding-left: 40px;">A Fir 12" dia., bears N.30°45'E., 149 lks. mkd. ¼ S BT.</p> <p style="padding-left: 40px;">A S.Pine 30" dia., bears S.36°30'W., 112 lks., mkd ¼ S BT.</p>
<p>Ben B. Irving - June 1930 - C.S. File 46/109; C.S. File 37/23 and RM 1-11</p> <p>-----</p> <p>Found - 6" x 12" x 6" above ground slate (or schist) stone as described in govt. field notes. BTs in good condition, did not chop out, but reblazed and scribed:</p> <p style="padding-left: 40px;">12" Fir now 18", N.30°45'E., 149 lks.</p> <p style="padding-left: 40px;">30" Sugar Pine now 36", S.36°30'W., 112 lks.</p>
<p>BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #'s 350 and 818, surveyed Aug. 1973/May 1974 - (DCSO records Vol. 38 Page(s) 15631-32)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 2 and 3, monumented with the original slate stone, 18x12x6", firmly set 12" in the ground, mkd. ¼ on W. face, from which the original bearing trees:</p> <p style="padding-left: 40px;">A Fir 32" dia., bears N.30¾°E., 149 lks. with healed blaze</p> <p style="padding-left: 40px;">A Sugar Pine 51" dia., bears S.36½°W., 115 lks., with healed blaze. (Rec. 112 lks. to face.)</p> <p>At the corner point</p> <p>Set an iron post, 28" long, 2½ dia., 24" in the ground, with brass cap marked</p> <p style="padding-left: 100px;">T 33 S R 5 W</p> <p style="padding-left: 100px;">¼</p> <p style="padding-left: 100px;">S 3   S 2</p> <p style="padding-left: 100px;">1974</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A Fir 18" dia., bears N.60°E., 61½ lks., mkd. ¼ S2 BT.</p> <p style="padding-left: 40px;">Deposit corner stone alongside iron post.</p>
<p>Fd. OK by K. DeGroot, Dec. 1999 - M133-78</p>
<p>Ron Quimby - Crew: N. Fromdahl &amp; R. Olsen - 6/2015 - C.S. File 65/89-7</p> <p>-----</p> <p>Found - BLM brass cap (properly mkd)</p> <p style="padding-left: 40px;">41" Fir N.30¾°E., 98.3 ft. good scar.</p> <p style="padding-left: 40px;">56" S.Pine S.36½°W., 75.9 ft. good scar.</p> <p style="padding-left: 40px;">29" Fir N.60°E., 40.6 ft. good scar.</p> <p>continued next page</p>

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - 11" Chincapin N.29°W., 24.4 ft. scribed ¼ S3 BT.  
Note - Hand held Lat: N 42°43.917' Long: W 123°16.168'  
Compass decl. 15½°E.