

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8967)

Set granite stone 16 x 8 x 5 ins., 11" in the ground for ¼ sec. cor. marked ¼ on N. side, from which
A Fir 24" dia., bears N.27°30'E., 53 lks. marked ¼ S BT.
A Fir 24" dia., bears S.41°W., 44 lks., marked ¼ S BT.

Ben B. Irving - June 1930 - C.S. File 46/109; C.S. File 37/23 and RM 1-11

5" x 8" x 6" above ground granite boulder as described in govt. field notes. O.B.T.s in excellent condition, one having been chopped out, scribe marks legible. Reblazed and scribed in bark both trees.
24" Fir now 32", N.27°30'E., 53 lks.
24" Fir now 32", S.41°W., 44 lks.

Douglas Co. Surveyors Office - John M. Powell, Joe Brady, crew - Aug./Sept. 1967 - C.S. File 53/52-51

Found - Orig. 24" now 35" D.Fir N.27½°E., 35.0 ft., tree has been opened but pitched over. Also bark scribed.
Orig. 24" now 38" D.Fir S.41°W., 29.0 ft. bark scribed.
5/8" Iron rod at corner, not recorded.
Orig. stone, "¼" on North side.
New BT - 6" D.Fir N.52°E., 19.7 ft. mkd. ¼ S 2 CS BT.
This corner lies West of creek, approx. 120.0 ft.

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #'s 350 and 818, surveyed Aug. 1973/May 1974 - (DCSO records Vol. 38 Page(s) 15631)

The ¼ sec. cor., monumented with the original granite stone, 16 x 8 x 5 ins., firmly set 11" in the ground, mkd. ¼ on N. face, with an iron rod driven alongside 5/8" dia., firmly set, protruding 12" above ground, from which the original bearing trees:
A Fir 40" dia., bears N.27½°E., 53 lks. dist., with healed original blaze. This tree was rescribed by the County Surveyor, in 1930, with scribe marks ¼ S2 CS BT visible on bark.
A Fir 36" dia., bears S.41°W., 44 lks. dist., with healed blaze. This tree was rescribed by the County Surveyor in 1930, with scribe marks 4S CS visible on partially open blaze.
(Cont. Next Page)

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a bearing tree mkd. by the County in 1967
A Fir 6" dia., bears N.52°E., 30 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 33 S R 5 W

¼ $\frac{S\ 2}{S\ 11}$
1974

Deposit corner stone and reset iron rod alongside iron post.

Fd. OK by K. DeGroot, Dec. 1999 - M133-78

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1355, survey Dec. 1986/June 1992 - (DCSO records C.S. File 64/76-5)

Ron Quimby - For: Plum Creek Timber Co. - 8/2015 - m166-39

Found - 2½" 1974 BLM brass cap
43" Fir N.27°E., 35.0' healed blaze low, visible bark scribe high.
18" Fir N.52°E., 19.7' healed double blaze
38" Fir S.41°W., 29.0' healed scar - partially visible bark scribes
New BT- 14" Fir N.18°W., 23.4' scribed "¼ S2 BT"

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24169-70)

The ¼ sec. cor. of secs. 2 and 11, reported by Nickerson in 1986-89; perpetuated by Quimby, in 2015; monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.

from which bearing trees reported by Nickerson

A fir, 43" dia., bears N.27½°E., 35.0 ft., with a healed blaze & illegible scribe marks visible on bark. (Orig)

A fir, 22" dia., bears N.52°E., 19.8 ft., with a healed double blaze.

A fir, 40" dia., bears S.41°W., 29.0 ft., with a healed blaze. (Original)

and a bearing tree mkd. by Quimby

A fir, 16" dia., bears N.19¼° W., 23.3 ft., with a healed blaze.

The geographic position in NAO 1983 (2011)

Latitude: 42°43'28.53" N. Longitude: 123°15'33.69" W.