

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 540640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

... private survey records referenced and the measurements of this survey; and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, with top flush with the surface of the ground, with aluminum cap (properly) mkd. from which the remains of bearing trees mkd. by Irving

- A rotted fir stump, 40" dia., bears S.88°E., 59.8 ft., with no marks visible on open blaze.
- A fir, 37" dia., bears N.87½°W., 23.0 ft., with no marks visible on open blaze.

and accessories established by DeGroot

- A fir, 17" dia., bears N.27°E., 26.5 ft., with a healed double blaze.
- A fir, 24" dia., bears S.25¾°E., 40.2 ft., with a healed double blaze.
- An iron rod, 5/8" dia., firmly set, projecting 3" above the ground, bears S.26°11'52"W., 24.95 ft., with yellow plastic cap mkd. BTS ENG. SURV.
- An iron rod, 5/8" dia., firmly set, with top 6" below the surface of the ground, bears N.25°41'57"W., 25.00 ft., with yellow plastic cap mkd. BTS ENG. SURV.

The iron pipe set by Irving was not recovered.