

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ben B. Irving - June 1930 - C.S. File 46/109; C.S. File 37/23 and RM 1-11

Placed on township line midway between section corners.
Drove 1 1/4" x 42" I.P., 36" in ground for corner. 6" x 8" x 60" Yew wood post alongside scribed CC 1/4 S2 on South face and CS on North face.
20" Fir, South 73 lks, blazed and scribed CC 1/4 S2 CS BT.
20" Fir, S.58°E., 64 lks. blazed & scribed CC 1/4 S2 CS BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - August 1967 - C.S. File 53/52-13

Found - 1 1/2" Iron pipe, 1 ft. under ground and wood stake scribed CC 1/4 S2 CS.
20" now 24" D.Fir stump, South 48.1 ft., opened for scribe.
39" D.Fir S.58°E., 42.2 ft., shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T32S R5W
1/4 S 2
T33S R5W
1967

New BT - 8" Laurel S.69°W., 15.6 ft. mkd. 1/4 S2 CS BT.
This corner lies at fence corner running South and East.

Douglas Co. Surveyors Office - Stephen J. Flause, Deputy - Bill Stewart, crew - July 29, 1980 - C.S. File 61/11-10

Found - 1967 DCS0 brass cap properly marked, on a 1" I.P. firmly set and protruding 1.0 ft. from a rough pile of stone.
A 1 1/2" I.P. is found set flush with soil on the southeast edge of the brass cap/iron pipe.
An orig. 20" Fir now a decayed 24" x 54" high Fir stump, bears due South, 49.1 ft., 48.2 ft. to face. (Rec. South 48.2 ft.), opened blaze, has scribed "S" visible.
An orig. 20" Fir now a decayed 29" x 53" high Fir stump, bears S.51°E., 43.0 ft., 42.2 ft. to face. (Rec. S.58°E., 42.2 ft.) Upon partially opening a well healed blaze, the scribing "S2 CS" is found. A BLM BT tag on this stump records the bearing from tree to monument as N.52°W.
An 8" Madrone (Rec. Laurel) is still approx. 8" dia., Madrone bears S.69°W., 15.6 ft. Tree has partially healed double blaze with scribing "S2 CS" visible. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Because both face measurements from orig. BTs to brass cap and 1½" I.P agree with record and bearing to due South BT is found to agree, the monument position is accepted as good. More stones are added to rough pile around monument and the brass cap now protrudes 7" above this pile.

New BTs -A 10" D.Fir bears N.74°W., 35.0 ft. scribed "CC ¼ S2 CS BT" on a double blaze.

A 10" D.Fir bears N.41½°E., 71.9 ft. scribed "CC ¼ S2 CS BT" on a double blaze.

New trees and due South OBT stump are tagged with DCSO BT tags. Cap is located 30.0 ft. South of BLM road 31-5-35.1

Ron Quimby - For: Plum Creek Timber Co. - 8/2015 - m166-39

Found - 2½" 1967 DCSO brass cap
14" Fir N.41°E., 71.9' healed double blaze
19" Fir N.74°W., 35.0' healed double blaze
24"x54" tall fir stump South 49.1' rotten partial blaze

8" Madrone (dead) S.69°W., 15.6' healed double blaze
New BTs- 6" Fir S.47°E., 16.9'
8" Fir S.19°W., 12.2'
Both scribed "¼ S2 BT"

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24111-2)

The ¼ sec. cor. of sec. 2 only, established by Irving, Douglas County Deputy Surveyor, in 1930; perpetuated by the Douglas County Surveyor's Office in 1967 and again in 1980; subsequently perpetuated by Quimby, in 2015; and is accepted as the cor.; monumented with an iron post, 1" dia., firmly set, projecting 6" above a mound of stone, 3 ft. base, 12" high, with brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Irving
A rotted fir stump, size indeterminate, bears S.0½°W., 48.7 ft., no marks visible.

and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1967

A madrone snag, 6" dia., bears S.69°W., 15.6 ft., with a healed double blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office in 1980

A fir, 16" dia., bears N.41¾°E., 71.5 ft., with a healed blaze.

A fir, 22" dia., bears N.74¾°W., 34.9 ft., with a healed blaze.

continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Quimby
A fir, 6" dia., bears S.43³/₄°E., 16.9 ft., with illegible
scribe marks visible on partially healed blaze.
A fir, 9" dia., bears S.19°W., 12.2 ft., with no marks
visible on partially healed blaze.