

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8952)

Set basaltic stone 10 x 10 x 10 ins., 7" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 18" dia., bears N.19°E., 200 lks. dist. marked ¼ S BT.
A Fir 8" dia., bears S.50°W., 416 lks. dist. marked ¼ S BT.

BLM remonumentation by Joseph S. Gawron, John M. Jelley and Rollin D. Aanrud, Cadastral Surveyors, under Group #'s 350 and 566, surveyed March 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 13980)

The ¼ sec. cor., monumented with a basalt stone, 14 x 12 x 10 ins., firmly set, 8" in the ground, mkd. ¼ on W. face, from which the original bearing trees:
A Fir 38" dia., bears N.20°E., 200 lks. dist., with scribe marks ¼ visible on partly opened blaze. (Rec. N.19°E.)
A Fir stump, 24" dia., bears S.49½°W., 411 lks. dist., with rotted blaze. (Rec. S.50°W., 416 lks.)

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 33 S R 5 W
¼
S 14 S 13
1967

from which a new bearing tree
A Fir 31" dia., bears N.54°W., 35½ lks. dist., mkd. ¼ S14 BT.
Deposit the corner stone alongside the iron post.