

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8952-53)

Set basaltic stone 20 x 8 x 6", 20" in the ground at the foot of a sloping bluff, 40 ft. high for cor. to secs. 11, 12, 13 and 14, marked with 4 notches on the S. and 1 notch on the E. edges, from which

- A Cedar 24" dia., bears N.51°E., 60 lks. dist., marked T33S R5W S12 BT.
- A Fir 18" dia., bears S.21°30'E., 78 lks. dist., marked T33S R5W S13 BT.
- A Cedar 24" dia., bears S.16°30'W., 74 lks. dist., marked T33S R5W S14 BT.
- A Fir 24" dia., bears S.14°30'W., 121 lks. dist., marked T33S R5W S11 BT.

BLM remonumentation by Joseph S. Gawron, John M. Jelley and Rollin D. Aanrud, Cadastral Surveyors, under Group #'s 350 and 566, surveyed March 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 13980-81)

The Sec. cor., monumented with the original basalt stone, 20 x 8 x 6", firmly set 10" in the ground, mkd. with 4 notches on S. and 1 notch on E. edge, from which the original bearing trees:

- A Cedar snag, 24" dia., bears N.48½°E., 56 lks. dist., with scribe marks S3 5W 12 visible on partly opened blaze. (Rec. N.51°E., 60 lks.)
- A Fir 34" dia., bears S.25°E., 78 lks. dist., with healed blaze. (Rec. S.21½°E.)
- A Cedar 31" dia., bears S.14½°W., 72 lks. dist., with scribe marks 5W S14 visible on partly healed blaze. (Rec. S.16½°W., 74 lks.)
- A Fir snag, 29" dia., bears N.17°W., 119 lks. dist., with scribe marks 33S 5W visible on partly opened blaze. (Rec. N.14½°W., 121 lks.)

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked

T 33	S R	5 W
S 11		S 12
S 14		S 13

from which new bearing trees

- A Fir 11" dia. bears N.54°E. 56 lks. mkd. T33S R5W S12 BT
- A Fir 12" dia. bears N.60°W. 19½ lks. mkd. T33S R5W S11 BT

Deposit the corner stone alongside the iron post.

continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec Cor for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1355, survey Dec. 1986/June 1992 - (DCSO records C.S. File 64/76-5)

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24120)

The cor. of secs. 11, 12, 13, and 14, reported by Rambo in 2010-11, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd from which the remains of bearing trees reported by Rambo

A cedar snag, 29" dia., bears N.51¼°E., 37.0 ft., with scribe marks 3 S 12 BT visible on partially healed blaze. (Original)

A fir, 20" dia., bears N.57°E., 37.5 ft., with a healed blaze.

A fir, 46" dia., bears S.21½°E., 51.5 ft., with a healed blaze. (Original)

A cedar, 35" dia., bears S.17°W., 47.5 ft., with illegible scribe marks visible on partially healed blaze. (Original)

A fir snag, 29" dia., bears N.11¼°W., 76.9 ft., with scribe marks 3S 5W BT visible on partially healed blaze. (Record, N.17°W., 78.5 ft.)

The cor. is located at the base of a rock bluff, 45 ft. high., base bears SE and NW.