

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8955)

Set basaltic stone 12 x 8 x 6 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. side, from which
A Cedar 8" dia., bears N.22°W., 33 lks. dist., mkd. ¼ S BT
A Fir 18" dia., bears S.54°E., 27 lks. dist., mkd. ¼ S BT.

Survey by Norman D. Price - July 1953 - C.S. File 41/184

Found - A granite stone 10 x 8 ins., firmly set flush with top of ground, mkd. ¼ on W. face, from which the original bearing trees:
A D.Fir 36" dia., bears S.54°E., 18 ft. dist., with blaze healed.
An Incense Cedar 18" dia., bears N.23½°W., 22.4 ft. dist., with scribe marks ¼ S uncovered.
Against N. side of stone, Set an iron pipe 3 ft. long, 1¼" dia., 28" in the ground mkd. RS33.

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #'s 350 and 818, surveyed Aug. 1973/May 1974 - (DCSO records Vol. 38 Page(s) 15629-30)

The ¼ sec. cor., monumented with the original basalt stone, 12x8x6 ins., firmly set 10" in the ground, mkd. ¼ on W. face, from which the remains of the original bearing trees:
A Fir stump 26" dia., bears S.54°E., 27 lks. dist., with illegible scribe marks visible on partially open blaze.
A Cedar 18" dia., bears N.22°W., 33 lks. dist., with scribe marks BT visible on partially open blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 33 S R 5 W
¼
S 11 | S 12
1974

from which new bearing trees
A Cedar 22" dia., bears S.77°E., 28½ lks. dist., mkd. ¼ S12 BT.
A Cedar 14" dia., bears N.57½°W., 143½ lks. dist., mkd. ¼ S11 BT.
Deposit corner stone alongside iron post.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1355, survey Dec. 1986/June 1989 (DCS0 records C.S. File 64/76-5 BLM pg # 3 & 4)

The ¼ sec. cor. of secs. 11 and 12, monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A fir snag, 26" dia., bears S.54°E., 27 lks., with illegible scribe marks visible on partially healed blaze.
- A cedar snag, 18" dia., bears N.22°W., 33 lks., with healed blaze.

and bearing trees mkd. by Roseberry and Evans

- A cedar, 25" dia., bears S.77°E., 28½ lks., with illegible scribe marks visible on partially healed blaze.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCS0 records Vol. 59 Page(s) 24176-7)

The ¼ sec. cor. of secs. 11 and 12, reported by Nickerson in 1986-89, monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd. from which the remains of bearing trees reported by Nickerson

- A cedar, 31" dia., bears S.77°E., 18.8 ft., with a healed blaze.
- A fir snag, 27" dia., bears S.54°E., 17.8 ft., with a healed blaze. (Original)
- A cedar, 28" dia., bears N.57½°W., 94.7 ft., with a healed blaze.
- A rotted cedar snag, size indeterminate, bears N.22°W., 21.8 ft., no marks visible. (Original)