

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8957)

-----  
Set a basaltic stone 12 x 10 x 8 ins., 8" in the ground for 1/4 sec. cor. marked 1/4 on W. side, from which  
A S.Pine 30" dia., bears N.41°W., 39 lks. dist. mkd. 1/4 S BT.  
A Fir 10" dia., bears S.39°30'E., 91 lks. dist. mkd. 1/4 SBT

Survey by Ben B. Irving - June 1930 - C.S. File 46/109; C.S. File 37/23 and RM 1-11

-----  
Rock, serpentine, not basaltic, as called for in govt. field notes. O.B.T.s alive and in excellent shape.  
30" Sugar Pine N.41°W., 39 lks.  
10" Fir S.39°30'E., 91 lks.

George J. Wenderoth - 1955 - C.S. File 46/109

-----  
1 1/4" Iron pipe, from which  
30" Pine N.41°W., 25.7 ft.  
10" Fir S.39°30'E., 60.0 ft.

BLM remonumentation by Joseph Gawron, John Jelley and Rollin Aanrud, Cadastral Surveyors, under Group #'s 350 and 566, surveyed March 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 13982)

-----  
The 1/4 sec. cor., monumented with the original basalt stone, 12 x 10 x 8 ins., firmly set 8" in the ground, mkd. 1/4 on the W. face, alongside of which is driven an iron pipe, 1 1/2" dia., firmly set, protruding 16" from the ground, from which the original bearing trees:

A Sugar Pine 36" dia., bears N.41°W., 39 lks. dist., with scribe marks 1/4 S visible on a partially healed blaze.  
A D.Fir 20" dia., bears S.39 1/2°E., 91 lks. dist., with scribe marks 1/4 S visible on an opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 33 S R 5 W  
1/4  
S 2 | S 1  
1965

from which

A D.Fir 8" dia., bears S.70°E., 68 lks. dist., mkd. 1/4 S1 BT.

(Cont. Next Page)

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

|   |
|---|
| A D.Fir 6" dia., bears S.3°W., 53 lks. dist., mkd. ¼ S2 BT<br>Deposit the corner stone and bury the iron pipe alongside<br>the iron post. |
| Cor. Fd. OK, in BLM survey by Roseberry, Group #723, 1970<br>(DCSO records, Vol. 36 Pg. 14829)  |
| Fd. OK by K. DeGroot, Dec. 1999 - M133-78   |
| Fd. OK by R. Wytcherley, July 2003 - M142-66  |
|   |