

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8953-54)

Set basaltic stone 12 x 6 x 6 ins., 8" in the ground for 1/4 sec. cor. marked 1/4 on the N. side, from which
A Fir 10" dia., bears N.9°W., 10 lks. dist., mkd. 1/4 S BT.
A Fir 8" dia., bears S.43°E., 31 lks. dist., mkd. 1/4 S BT.

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #'s 350 and 818, surveyed Aug. 1973/May 1974 - (DCSO records Vol. 38 Page(s) 15629)

The 1/4 sec. cor., monumented with the original basalt stone, 12 x 6 x 6 ins., firmly set 6" in the ground, mkd. 1/4 on N. face, from which the original bearing trees:

- A Fir 13" dia., bears N.9°W., 10 lks. dist., with scribe marks 1/4 S visible on partially open blaze.
- A Fir 16" dia., bears S.43°E., 31 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked T 33 S R 5 W

1/4 S 12
S 13

1974

from which a new bearing tree

- A Fir 27" dia., bears N53 1/2°E., 26 lks. dist., mkd. 1/4 S12 BT.

Deposit corner stone alongside iron post.

Corner is located 42 lks. West of a creek, 5 lks. wide, course N.20°W.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24119)

The 1/4 sec. cor. of secs. 12 and 13, reported by Roseberry and Evans in 1973-74, monumented with an iron post, 2 1/2" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.

from which the remains of BTs reported by Roseberry and Evans

- A fir, 39" dia., bears N.53 1/2°E., 17.2 ft., with a healed blaze.
- A fir, 25" dia., bears S.43°E., 20.5 ft., with a healed blaze. (Original)
- A fir snag, 13" dia., bears N.9°W., 6.6 ft., with scribe marks 1/4 S visible on open blaze. (Original) Cont.

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

The geographic position in NAD 1983 (2011)
Latitude: 42°42'35.58" N. Longitude: 123°14'21.66" W.