

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8956)

-----  
Set a basaltic stone 20 x 12 x 8 ins., 15" in the ground for 1/4 sec. cor. marked 1/4 on N. side from which  
A Fir 16" dia., bears S.39°W., 23 lks. dist. mkd. 1/4 S BT.  
A Fir 12" dia., bears N.43°E., 14 lks. dist. mkd. 1/4 S BT.

BLM remonumentation by Joseph S. Gawron, John M. Jelley and Rollin D. Aanrud, Cadastral Surveyors, under Group #'s 350 and 566, surveyed March 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 13981-82)

-----  
The 1/4 sec. cor., monumented with the original basalt stone 20 x 12 x 8 ins., firmly set 12" in the ground, mkd. 1/4 on the N. face, from which the original bearing trees:

A Fir 16" dia., bears N.43°E., 23 lks. dist., with scribe marks BT visible on partly healed blaze. (Rec. 14 lks.)  
A Fir 14" dia., bears S.39°W., 14 lks. dist., mkd. 1/4 S BT on opened blaze. (Rec. 23 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 33 S R 5 W  
1/4  $\frac{S 1}{S 12}$   
1966

from which new bearing trees

A Fir 12" dia., bears N.3°E., 19 lks. dist., mkd. 1/4 S1 BT.  
A Fir 14" dia., bears S.5°W., 42 lks. dist., mkd. 1/4 S12 BT  
Deposit the corner stone alongside the iron post.

Cor. Fd. & used in BLM survey by Roseberry, under Group #723, surveyed Nov/Dec. 1970 (DCSO records, Vol. 36 Pg. 14827)

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24175-6)

-----  
The 1/4 sec. cor. of secs. 1 & 12, reported by Roseberry in 1970, monumented with an iron post, 2 1/2" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which the remains of bearing trees reported by Roseberry  
A fir, 16" dia., bears N.3°E., 12.5 ft., with a healed blaze.

A fir snag, 17" dia., bears N.43°E., 14.0 ft., with no marks visible on open blaze. (Orig) (Record, 15.2 ft.)  
continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 16" dia., bears S.5°W., 26.3 ft., with a healed blaze. (Record, 27.7 ft.)

A fir, 16" dia., bears S.39°W., 9.2 ft., with a healed blaze. (Original)