

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM survey by Joseph S. Gawron, John Jelley and Rollin Aanrud, Cadastral surveyors, under Group #'s 350 and 566, surveyed, March 1965/Dec. 1967 (DCSO records Vol. 34 Page(s) 13973)

Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only, at mid-point longitudinally between the theoretical intersection of the north and east boundaries of sec. 1 and the closing corner of sections 1 and 2.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap marked

$\frac{1}{4}$ S 1
T 33 S R 5 W
1965

from which

A D.Fir 12" dia., bears S.38°E., 49 lks. dist., mkd. $\frac{1}{4}$ S1
BT.

A D.Fir 6" dia., bears S.46°W., 43 lks. dist., mkd. $\frac{1}{4}$ S1
BT.