

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 647700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only, T32-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Lloyd D. Smith L.S. #1101 - For: Oregon State Board of Forestry - May 14, 1982 - M 92-34

Set Oregon State Board of Forestry 1½" x 36" galv. I.P. with a 3" bronze cap, 32" in ground.

New BTs -36" x 3 ft. high stump bears N.46½°E., 18.7 ft.

25" Fir bears N.57°W., 80.9 ft.

4" Canyon Live Oak bears N.64°E., 3.0 ft.

BT distances were measured to the face of the trees.

James McIntosh - For: State of Oregon, Dept. of Forestry - April 2012 - M 163-54

Found - OSBF P/C (1½"x36" galvanized iron pipe with 3" bronze cap) 1982, in place.

36"x3' high stump N.46½°E., 18.7' (now in place, scribes visible)

25" Fir N.57°W., 80.9' (now 31" in place, face closed, added BT tag)

YMLP (Yellow metal location poster) on 4" canyon live oak N.64°E., 3.0' (now 5" in place)

New - WP (Orange carsonite marker CBM-250 labeled Witness post) S.12°E., 3.10' to base

WP S.66°W., 2.40' to base

YMLP on 11" ponderosa pine S.50°W., 75.0' on west side of Quines Creek gravel road