

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36, T32-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 20 Page(s) 8455)

-----  
Set post corner of townships 32 and 33, S. Ranges 4 and 5 W., on NW. slope of mountain, from which  
A Fir 12" dia., bears S.60°W., 17 lks.  
A Fir 11" dia., bears N.62°W., 20 lks.  
A Fir 12" dia., bears N.42°E., 27 lks.  
A Redwood 36" dia., bears S.58°E., 39 lks.

Cor. Fd. and used in GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records, Vol. 21 Page 8959 and on page 8960, "I destroyed the marks on the SE and SW trees, also the marks on the SE and SW sides of the post, and notches on the S. side.

GLO survey by Carl S. Nicklin, under Contract #664, dated May 23, 1896 (DCSO records, Vol. 20 Page 8476)

-----  
The corner of Tps. 32 and 33 S., Rs. 4 and 5 W., bearing trees all standing; post badly decayed; bearing trees agree with description of the surveyor general. I fail to find any closing corner described by the surveyor general as 370 lks. W. of the corner of Tps. 32 and 33 S., Rs. 4 and 5 W., which I reestablished to refer to Tps. 32 and 33 S., R 5 W.

(Same surveyor, Page 8478)  
I reestablish as follows:  
Set a basalt stone 12 x 12 x 8 ins., 8" in the ground for corner of Ts. 32 and 33 S., R5W, marked with 6 notches on N. and W. edges, from which  
A Fir 12" dia., bears S.48°W., 22 lks. dist. mkd. T33S R5W S1 BT.  
A Fir 12" dia., bears N.85°W., 20 lks. dist. mkd. T32S R5W S36 BT.  
This cor. is on the NW. slope of mountain.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8628)

-----  
SE. cor. of Sec. 36, old post gone, I reestablished this cor. by setting a basalt stone, 12x10x10 ins., 8" in the ground, marked with 6 notches on the S. and W. edges, witnessed as described by the surveyor general.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36, T32-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wit:  
 Wm. Stoffel; Mike Darby; Mike Stone - June 1964 - C.S. File  
 53/52-62

-----  
 Found - D.Fir now 24" dia., S.60°W., 11.2 ft. Scribing  
 visible on partly exposed face "R 5 W". Tree  
 alive and in good condition.  
 D.Fir now 23" dia., N.62°W., 13.2 ft. Previously  
 opened, but nearly healed over, now scribing  
 visible. Tree in good condition.  
 (Cont. Next Page)

D.Fir now 26" dia., N.42°E., 21.8 ft. (not 17.8  
 ft.), scribing visible on partially exposed face  
 "S31". Tree in good condition.  
 Partly rotten Cedar stump, S.58°E., 25.7 ft. Scribing  
 visible "R 4 W T 33 S S 6".

Set Brass cap at cor. mkd: County Surveyors Office  

T	32	S
R	S 36	S R
5	S 1	31 4
W	1964	W

Did not mark any new trees.

BLM dependent resurvey by Joseph Gawron; John Jelley; Rollin  
 Aanrud, Cadastral surveyors, under Group #'s 350 and 566,  
 surveyed, March 1965/Dec. 1967 (DCSO records Vol. 34 Page(s)  
 13971-72)

-----  
 The corner of Tps. 32 and 33 S., R5W., only on the W. bdy. of  
 sec. 31, T32S R4W., monumented with an iron post, 1½" dia.,  
 firmly set, protruding 16" from the ground, with 1964 DCSO  
 marked brass cap, from which the original bearing trees mkd.  
 by Ives and Hyde in 1854

A D.Fir 20" dia., bears N.42°E., 27 lks. dist., with a  
 healed blaze.  
 An Incense Cedar stub 48" dia., bears S.58°E., 39 lks.  
 dist., mkd. T32S R4W S BT on a weathered blaze.  
 A D.Fir 20" dia., bears S.60°W., 17 lks. dist., with a  
 healed blaze.  
 A D.Fir 18" dia., bears N.62°W., 20 lks. dist., with a  
 healed blaze.

add new bearing trees

An Incense Cedar 10" dia., bears N.28°W., 79 lks. dist.,  
 mkd. T32S R5W S36 BT.  
 A D.Fir 10" dia., bears S.53°W., 92 lks. dist., mkd. T33S  
 R5W S1 BT. (Cont. Next Page)

