

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18 of T33-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by McKenzie and Eckleson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records Vol. 21 Page(s) 8923)</p> <p>-----</p> <p>Set post for ¼ sec. cor., from which</p> <ul style="list-style-type: none">A Fir 6" dia., bears S.24°W., 22 lks. dist.A Fir 24" dia., bears S.76°E., 17 lks. dist.
<p>GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8925)</p> <p>-----</p> <p>Set a basaltic stone 20 x 10 x 10 ins., 14" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which</p> <ul style="list-style-type: none">A Fir 18" dia., bears S.45°30'E., 78 lks. dist., marked ¼ S BT.A Fir 20" dia., bears N.58°W., 27 lks. dist., marked ¼ S BT.
<p>BLM remonumentation by James E. Jelley, Cadastral Surveyor, under Group #350, surveyed April 1962 (DCSO records Vol. 33 Page(s) 13923)</p> <p>-----</p> <p>The ¼ sec. cor., monumented with an unmarked basalt stone, 20 x 10 x 10 ins., firmly set, 10" in a mound of stone, 3 ft. base, 2 ft. high, from which the original bearing trees:</p> <ul style="list-style-type: none">A Fir 22" dia., bears S.50°E., 31 lks. dist., with scribe marks ¼ S visible on partly healed blaze. Reblaze and mark ¼ S18 BT, below old blaze. (Rec. S.45½°E., 78 lks.)A Fir 25" dia., bears N.50°W., 82 lks. dist., with healed blaze. Reblaze and mark ¼ S13 BT, below old blaze. (Rec. N.58°W., 27 lks.) <p>Sharp apparently reversed the distances to these trees.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. dia., 14 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap marked</p> <p style="text-align: center;">¼ S 13 S 18 R 5 W R 4 W T 33 S 1962</p> <p>Deposit the original corner stone alongside the iron post.</p>
<p style="text-align: right;">1</p>