

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; & 7 & 18, T33-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by McKenzie and Eckleson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records Vol. 21 Page(s) 8923)

Set post for cor. to secs. 7, 12, 13 and 18, from which
A Fir 10" dia., bears S.60°W., 34 lks. dist.
A Cedar 12" dia., bears N.45°W., 26 lks. dist.
A Cedar 18" dia., bears N.50°E., 54 lks. dist.
A Cedar 12" dia., bears S.45°E., 2 lks. dist.

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8926)

Set a basaltic stone 24 x 16 x 14 ins., 18" in the ground, for cor. to secs. 7, 12, 13, and 18, marked with 4 notches on S. sides and 2 notches on N. side, from which
A Fir 24" dia., bears N.56°E., 31 lks. dist., marked T33S R4W S7 BT.
A W.Fir 10" dia., bears S.41°E., 32 lks. dist., marked T33S R4W S18 BT.
A Cedar 16" dia., bears S.12°W., 30 lks. dist., marked T33S R5W S13 BT.
A W.Fir 18" dia., bears N.15°W., 31 lks. dist., marked T33S R5W S12 BT.

BLM resurvey by Lynn Roseberry and Larry Evans, Cadastral Surveyors, under Group #'s 350 and 818, surveyed Aug. 1973/May 1974 - (DCSO records Vol. 38 Page(s) 15627)

The Sec. cor., on the E. bdy. of the Tp., monumented with the original basalt stone, 24 x 16 x 14 ins., firmly set 18" in the ground, mkd. with 2 notches on N. and 4 notches on S. edges, from which the original bearing trees:

A Fir 31" dia., bears N.56°E., 31 lks. dist., with healed double blaze.
A W.Fir 15" dia., bears S.39°E., 32 lks. dist., with healed double blaze. (Rec. S.41°E.)
A Cedar 21" dia., bears S.12°W., 30 lks. dist., with healed double blaze.
A W.Fir 20" dia., bears N.15°W., 29½ lks. dist., with healed double blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked
(Cont. Next Page)

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T33-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 33 S
R 5 W R 4 W
S 12 S 7
S 13 S 1
1974

from which new bearing trees
A Yew 6" dia., bears S.60°E., 21 lks. dist., mkd. T33S R4W
S18 BT.
A Cedar 11" dia., bears N.68°W., 59½ lks. dist., mkd. T33S
R5W S12 BT.
Deposit corner stone alongside iron post.