

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; and 7 of T33-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by McKenzie and Eckleson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records Vol. 21 Page(s) 8923)

-----  
Set post for ¼ sec. cor., from which  
A Live Oak 10" dia., bears S.10°E., 25 lks. dist.  
A Fir 14" dia., bears N.45°W., 12 lks. dist.

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8926-27)

-----  
Set basaltic stone 18 x 10 x 12 ins., 12" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which  
A Cedar 10" dia., bears N.73°E., 19 lks. marked ¼ S BT.  
A Cedar 24" dia., bears S.26°W., 30 lks. marked ¼ S BT.

BLM remonumentation by Lynn M. Roseberry, Cadastral Surveyor, Group #'s 936 and 1000, July 1977/April 1980 - (DCSO records Vol. 42 Page(s) 16643-44)

-----  
The ¼ sec. cor., monumented with the original basalt stone, 18 x 12 x 10 ins., firmly set 12" in the ground, mkd. ¼ on W. face, from which the remains of the original bearing trees:  
A Cedar 12" dia., bears N.73°E., 19 lks. dist., with scribe mark S visible on partially opened double blaze.  
A root hole bears S.26°W., 30 lks., dist., with a down Cedar alongside, 28" dia., with healed double blaze.

At the corner point  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap marked  
T 33 S  
R 5 W 1/4 R 4 W  
S 12 | S 7  
1980

from which a new bearing tree  
A Fir 28" dia., bears S.21½°W., 39 lks., mkd. ¼ S12 BT.  
Deposit corner stone alongside iron post.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24176)

-----  
The ¼ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., reported by Roseberry in 1977-80, monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, in a mound of stone, 3 ft. base, to the top, with brass cap (properly) mkd.  
Continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; and 7 of T33-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees reported by Roseberry  
A cedar, 9" dia., bears N.79½°E., 12.0 ft., with scribe  
mark S visible on partially open blaze. (Original)  
(Record, N.73°E., 12.5 ft.)  
A fir, 34" dia., bears S.10°W., 25.7 ft., with a healed  
blaze. (Record, S.21½°W.)