

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6 of T33-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by McKenzie & Eckleson Dep Surveyors under Contract #328 dated June 17, 1879 (DCSO rec Vol. 21 Page 8924)</p> <p>-----</p> <p>Set post for ¼ sec. cor., from which</p> <ul style="list-style-type: none">A Laurel 10" dia., bears S.49°E., 40 lks. dist.A Cedar 14" dia., bears N.87°W., 7 lks. dist.																								
<p>GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8928)</p> <p>-----</p> <p>Set a basaltic stone 12 x 8 x 6 ins., 8" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which</p> <ul style="list-style-type: none">A Y.Pine 24" dia., bears N.15°30'W., 165 lks. dist., marked ¼ S BT.A Cedar 5 ft. dia., bears S.41°E., 70 lks. mkd. ¼ S BT.																								
<p>BLM survey by Joseph Gawron, John Jelley, and Rollin Aanrud, Cadastral surveyors, under Group #'s 350 and 566, surveyed March 1965/Dec. 1967 (DCSO records Vol. 32 Page(s) 13976-77)</p> <p>-----</p> <p>The ¼ sec. cor., monumented with the original basalt stone, 12 x 8 x 6 ins., firmly set, 8" in the ground, mkd. ¼ on the W. face, from which the original bearing trees mkd. by Sharp:</p> <ul style="list-style-type: none">A Ponderosa Pine 30" dia., bears N.15½°W., 159 lks. dist., with a healed blaze. (Rec. 165 lks.)An Incense Cedar 60" dia., bears S.41°E., 70 lks. dist., with a weathered blaze, no marks discernible. <p>At the corner point</p> <p>Set an iron post, 28" long, 2½" dia., 24" in the ground, & in a mound of stone, 4 ft. base, to top, with brass cap mkd</p> <p style="text-align: center;">¼</p> <table style="margin-left: auto; margin-right: auto;"><tr><td>S</td><td>1</td><td> </td><td>S</td><td>6</td></tr><tr><td>R</td><td>5</td><td>W</td><td> </td><td>R</td><td>4</td><td>W</td></tr><tr><td colspan="6" style="text-align: center;">T 33 S</td></tr><tr><td colspan="6" style="text-align: center;">1965</td></tr></table> <p>from which</p> <ul style="list-style-type: none">An I.Cedar 10" dia., bears N.52°E., 72 lks. mkd. ¼ S6 BT.A P.Pine 15" dia., bears S.81°W., 53 lks. mkd. ¼ S1 BT. <p>Reset corner stone on W. side of iron post.</p>	S	1		S	6	R	5	W		R	4	W	T 33 S						1965					
S	1		S	6																				
R	5	W		R	4	W																		
T 33 S																								
1965																								
<p>Fd. 1965 Brass cap in BLM resurvey by Roseberry, under Group #723, surveyed Nov/Dec. 1970 (DCSO rec.s, Vol. 36 Page 14827)</p> <p>Fd. Ok by Ken Hoffine, 3/2005 - M147-57 A&B</p>																								
<p>1</p>																								