

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 932010

PRIMARY CORNER DESCRIPTION Cor. #2, Hard Times M.S.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey of the Mining Claim of R.C. Shipley, Hard Times Lode, by Norman D. Price, Mineral Surveyor - Surveyed June/July 1953 (DCSO records Vol. 28 Page(s) 11958)

Set a basalt stone 24 x 9 x 7 ins., 16" in the ground and in a mound of stone to top, mkd. HT-2-920; from which
A D.Fir 16" dia., bears S.30¼°W., 49.4 ft. dist., mkd. HT-2-920 BT.
A D.Fir 20" dia., bears S.63°W., 48.5 ft. dist., mkd. HT-2-920 BT.
A Corner of the location bears N.57°E., 48.4 ft. dist.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy, K. Cheney, crew - Oct. 12, 1976 - C.S. File 59/24-30

Found - An orig. 16" D.Fir now a 17" stump, bears S.30¼°W., 49.4 ft. with traces of scribing visible along the edges of an unhealed blaze. It appears as if the scribing has been chopped out.
An orig. 20" Fir now a 24" snag, bears S.63°W., 48.5 ft. with no marks visible on an unhealed blaze.
The orig. monument is gone.

An unrecorded 3/8" iron rod bears S.78°E., 1.3 ft.
Due to impending road construction in the area, we do not monument the true corner point.

We Set a Witness Corner as follows:

At a point 60.0 ft. East of the true corner point, We set a 1" x 30" Iron pipe 28" in the ground for the Witness corner with brass cap attached, stamped: Douglas Co. Surveyor

T 33 S R 5 W
Witness Cor.
/\ MS
Cor. 2 920
West 60 ft. to
True cor.
1976

New BTs -26" D.Fir bears N.75°E., 24.8 ft. scribed "WC HT 2 920 CS BT" on a double blaze.

12" Madrone bears S.21°W., 9.5 ft. scribed "WC HT 2 920 CS BT" on a double blaze.