

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 932040

PRIMARY CORNER DESCRIPTION Cor. #3, Hard Times M.S.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey of the Mining Claim of R.C. Shipley, Hard Times Lode, by Norman D. Price, Mineral Surveyor - Surveyed June/July 1953 - (DCSO records Vol. 28 Page(s) 11958)

Set a basalt stone 24 x 14 x 8 ins., 16" in the ground, and in a mound of stone to top, mkd. HT-3-920; from which
A D.Fir 28" dia., bears S.38°W., 55.5 ft. dist., mkd. HT-3-920 BT.
A Sugar Pine 16" dia., bears S.89½°W., 24.6 ft. dist., mkd. HT-3-920 BT.
A corner of the location bears S.11°47'E., 2.6 ft. dist.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - K. Cheney, crew - Oct. 14, 1976 - C.S. File 59/24-34

Found - A Basalt stone 20" x 12" x 8", 4" in ground (Rec. 24x14x8, 16" in ground) mkd. "HT 3-920"
28" D.Fir now 34", bears S.35°W., 55.5 ft. (Rec. S.38°W.) No blaze.
16" Sugar Pine now 24", bears S.85°W., 23.4 ft. (Rec. S.89½°W., 24.6 ft.) No blaze.

The two above trees have no apparent blazes or scribing as called for in the record "HT 3 920 BT".

Set a 1" x 30" galv. I.P. with brass cap 25" in ground mkd:
Douglas Co. Surveyor
T 33 S R 5 W
Cor. \ MS
3 / 920
1976

Set marked portion of stone 16"x10"x6" on East side of cap. Stone broke in half.

Set brass cap at orig. stone's location. Due to discrepancy in the bearing and dists. in the found BTs, calls from ravine, course S.70°W., 100 ft.; a trail, course S.72°W., 7 ft.; and a location marker, a 12" Fir stump 48" high with upper most 2½ ft. cut with axe 8" square, bearing S.11°47'E., 2.6 ft. dist. from corner, are used for evidence to show stone at true location.

New BTs -16" D.Fir bears S.88°E., 29.6 ft. double blazed and scribed "HT 3 920 CS BT"

16" Sugar Pine bears N.62°E., 36.8 ft. double blazed and scribed "HT 3 920 CS BT".