

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T33-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9002)

Set post cor. to secs. 7, 12, 13 and 18, from which
A Chinquapin 3" dia., bears N.25°W., 17 lks.
A Chinquapin 8" dia., bears N.46°E., 16 lks.
A Chinquapin 6" dia., bears S.34°E., 14 lks.
A Laurel 10" dia., bears S.38°W., 53 lks.

Cor. used in GLO survey by Byars, Group #431, dated March 1882 (DCSO records, Vol. 21 Pg. 9020 and Page 9029)

BLM dependent resurvey by Joseph S. Gawron under Group #'s 350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol. 33 Page(s) 13837-8)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 33 S
R 7 W R 6 W
S 12 S 7
S 13 S 18
1963

from which
A D.Fir 12" dia., bears N.39°E., 83 lks. dist., mkd. T33S R6W S7 BT.
A Ponderosa Pine 38" dia., bears S.34°E., 98 lks. dist., mkd. T33S R6W S18 BT.
A D.Fir 4" dia., bears S.57°W., 36 lks. dist. mkd. X BT.
A Chinquapin 6" dia., bears N.44°W., 90 lks. dist., mkd. T33S R7W S12 BT.