

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 1 of T33-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors,
under Contract #54, dated Feb. 19, 1855 (DCSO records Vol.
21 Page(s) 9001)

Set quarter sec. post on steep N. descent, from which
A Chinquapin 10" dia., bears N.14°W., 60 lks.
A Cedar 12" dia., bears S.40°E., 22 lks.

BLM dependent resurvey by Joseph S. Gawron under Group #'s
350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol.
33 Page(s) 13840)

Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in
the ground, with brass cap marked ¼

S 1 S 6
R 7 W R 6 W
T 33 S
1963

from which

A D.Fir 14" dia., bears N.17°E., 13½ lks. dist., mkd. ¼ S6
BT.

An I.Cedar 6" dia., bears N.10°W., 42 lks. dist., mkd. ¼
S1 BT.

Fd. and used in BLM survey by Jolley, Aanrud and Roseberry,
Group #'s 350 and 688, Survey, May 1969/March 1970 (DCSO
records, Vol. 35 Pg. 14472)

Cor. Fd. OK, by G. Nygren, March 1994, M 118-79