

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9020)

Set a Laurel post, 3 ft. long, 4" sq., 18" in the ground, mkd. $\frac{1}{4}$ S on N. face, for the $\frac{1}{4}$ sec. cor., from which
A Laurel 6" dia., bears N.5°E., 29 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Laurel 8" dia., bears S.60°W., 15 lks. dist. mkd. $\frac{1}{4}$ S BT.

BLM dependent resurvey by Joseph S. Gawron, Cadastral Surveyor, under Group #'s 350 and 526, surveyed Sept. 1963/ July 1964 - (DCSO records Vol. 33 Page(s) 13842-43)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. dia., 26 ins. in the ground, with brass cap marked
T 33 S R 6 W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{7}{18}$
1964

from which
A D.Fir 10" dia., bears N.57°E., 55 $\frac{1}{2}$ lks., mkd. $\frac{1}{4}$ S7 BT.
A D.Fir 16" dia., bears S.76°W., 39 lks., mkd. $\frac{1}{4}$ S18 BT.

James M.M McIntosh - For: State of Oregon - Dept. of Forestry - Feb. 2001 - M 136-74

Found - BLM 2 $\frac{1}{2}$ "x28" iron pipe w/brass cap, 1964 (in place)
10" Fir (1964) N.57°E., 55 $\frac{1}{2}$ lks. (now 21" in place, face closed) Added BT tag.
16" Fir (1964) S.76°w., 39 lks. (now 29" in place, face closed) Added BT tag.
New - 25" Fir N.01°E., 16.4' to alum. nail in BT face scribed " $\frac{1}{4}$ S7 BT", BT tag.
Orange carsonite marker CBM-250 labeled witness post S.05°E., 3.9' to base.

Fd. BC & 3 BTs, by Kris DeGroot - 11/2014 - M166-21