

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9023)

Set a Laurel post, 3 ft. long, 4" sq., 18" in the ground, mkd. 1/4 S on N. face, for the 1/4 sec. cor., from which
A Laurel 6" dia., bears N.72°E., 32 lks. dist. mkd. 1/4 S BT
A Fir 6" dia., bears S.5°E., 10 lks. dist. mkd. 1/4 S BT.

BLM dependent resurvey by Joseph S. Gawron, under Group #'s 350 and 526, surveyed 1963/1964 (DCSO records Vol. 33 Page(s) 13845-46)

The 1/4 sec. cor., determined from the remains of the original bearing trees:

- A Madrone stump, size indeterminate, bears N.72°E., 28 lks. dist., with no marks remaining. (Rec. 32 lks.)
- A D.Fir snag, 30" dia., bears S.5°E., 10 lks. dist., mkd. 1/4 S on opened blaze.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked

	T	33	S	R	6	W
			S		6	
1/4			S		7	
						1964

from which

- A D.Fir 8" dia., bears N.85°W., 81 lks. dist., mkd. 1/4 S6 BT.
- A D.Fir 24" dia., bears S.38°E., 88 lks. dist., mkd. 1/4 S7 BT.

Fd. OK, by G. Nygren, March 1994, M 118-79