

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 160600

PRIMARY CORNER DESCRIPTION E. 1/16 cor. betw. secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Joseph S. Gawron under Group #'s 350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol. 33 Page(s) 13845)

Set an iron post, 30" long, 2½" dia., 24" in the ground, with brass cap mkd. E 1/16 $\frac{S\ 6}{S\ 7}$
1964

from which

A D.Fir 8" dia., bears N.14°W., 32 lks. dist., mkd. E 1/16 S6 BT.

A D.Fir 12" dia., bears S.23°W., 94 lks. dist., mkd. E 1/16 S7 BT.

Survey by Robert M. Thompson - For: Superior Logging - C.S. File 55/27

Found - Brass cap on 2" Galv. I.Pipe as set in U.S. BLM 1964 survey and 1 BT with scribe visible:
10" D.Fir N.14°W., 20.8 ft. (Rec. 21.1 ft.)
The SW BT has been obliterated by road construction.
New BT - 18" D.Fir S.61°E., 95.9 ft. scribed "3683 1/16 S7 BT".

This corner lies just off the northerly edge of a newly constructed forest road switchback, running N, W and S.

Cor. FD. OK, G. Nygren, March 1994, M 118-79