

PRIMARY CORNER DESCRIPTION So. Cor. for Secs. 31 & 32 only, T32-6

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8643)

-----  
Set post cor. to secs. 31 and 32, from which  
A Laurel 24" dia., bears N.15°E., 7 lks. dist.  
A Laurel 8" dia., bears N.20°W., 30 lks. dist.

Wallace Owen - Asst. Engineer - For: Robert Dollar Co. - April 18, 1958 - C.S. File 42/354

-----  
Found - Corner in poor condition, from which  
Orig. 24" Laurel N.15°E., 7 lks., now missing  
Orig. 8" Laurel N.20°W., 30 lks. now a rotten stub  
Set the corner from the 8" Laurel using compass and chain.  
Drove a 7/8" rod and scribed:  
6" Laurel N.26°30'W., 18.1 ft. "S31 RS 424 BT"  
5" Laurel N.28°30'E., 32.3 ft. "S32 RS 424 BT"

Survey by Victor McLind - For: John Clive - Nov. 1975  
M 58-57

-----  
Rod missing.  
Set 2" x 2" Hub at corner, from which  
6" Laurel now 10", bears N.26½°W., 18.1 ft., scribes partially visible.  
5" Laurel now 9", bears N.28½°E., 32.3 ft., scribes partially visible.

Fd. BTs OK, April 1984, R. Thompson, RM 3-61

Survey by Max Hull - For: Gregory Forest Products - August 1990 - C.S. File 63/115 and M 112-14

-----  
Found - 13" dia. Madrone N.26½°W., 18.1 ft. blaze healed.  
12" dia. Madrone N.28½°E., 32.3 ft. blaze healed.  
Set 5/8" I.R. w/cap mkd. "Hull R.S. 901". I.R. 30" long.  
New BTs -10" D.Fir S.58°E., 34.0 ft. scribed.  
8" D.Fir S.23°W., 24.7 ft. scribed.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - 9/15/96 - C.S. 64/66-9

-----  
MON. Fd.- 5/8" I.R. protruding 3" above ground  
Bt's Fd.- 12" dia. Madrone, with a fully healed double blaze, bears N.33½°W., 18.1'.  
11" dia. Madrone, with a fully healed double blaze, bears N.26°E., 32.3'.

(Cont. Next Page)

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 177700

PRIMARY CORNER DESCRIPTION So. Cor. for Secs. 31 and 32 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

14" dia. D.Fir, with a partially healed double blaze, scribing visible "S BT" , bears S.58°E., 34'.  
10" dia. D.Fir with a partially healed double blaze, scribing visible "3 RS 90 BT", bears S.23°W., 24.7'.  
Mon. Set - 5/8" I.R. is referenced a 2 3/8" Dia. DCSO Brass cap on a 1 3/8" O.D. by 32" long Iron Pipe is set a referenced position. BC/IP protrudes 6" above ground.  
5/8" I.R. measured 31½" long is set along north edge of BC/IP, protruding 4" above ground.