

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9018)

Set a Fir post, 3 ft. long, 4" sq., 18" in the ground, mkd. 1/4 S on W. face, for the 1/4 sec. cor., from which
A B.Oak 10" dia., bears N.45°E., 25 lks. dist. mkd. 1/4 S BT
A Laurel 12" dia., bears West 14 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1052, surveyed June/Oct. 1982 - (DCSO records Vol. 46 Page(s) 17589)

The 1/4 sec. cor., determined at record bearing and distance from the remains of the original bearing trees
A B.Oak 22" dia., bears N.45°E., 25 lks. dist. with scribe marks BT visible in reverse and relief on overgrowth.
A root hole bears West, 14 lks.

At the corner point
Set an alum. post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with alum. cap marked
T 33 S R 6 W
1/4
S 18 | S 17
1982

from which new bearing trees
A Ponderosa Pine 29" dia., bears S.86 3/4°E., 62 1/2 lks. mkd. 1/4 S17 BT.
A Fir 24" dia., bears S.55 3/4°W., 83 lks. mkd. 1/4 S18 BT.

James M. McIntosh - For: State of Oregon - Dept. of Forestry - Feb. 2001 - M 136-74

Found - BLM 2 1/2"x28" iron pipe w/alum. cap, 1982 (in place)
10" B.Oak (1882) N.45°E., 25 lks. (now 20" in place, face closed added BT tag.
12" Laurel (1882) West 14 lks. (now depression in place)
29" P.Pine (1982) S.86 3/4°E., 62 1/2 lks. (now 32" in place, face closed, BT tag)
24" Fir (1982) S.55 3/4°W., 83 lks (now 29" in place face closed, BT tag)
New - Orange carsonite marker CBM-250 labeled witness post N.33°W., 3.50' to base.
Orange carsonite marker CBM-250 labeled witness post S.36°E., 3.45' to base.

Fd. BC & 3 BTs, by Kris DeGroot - 11/2014 - M166-21