

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9018-19)

-----  
Set a Chinquapin post, 4 ft. long, 4" sq., 20" in the ground, marked T33S R6W S8 on NE. face; S17 on SE. face; S18 on SW. face; and S7 on NW. face, also 4 notches on South and 5 notches on East angles of same, for the cor. to secs. 7, 8, 17 and 18, from which

- A Fir 20" dia., bears N.46°E., 22 lks. dist. mkd. T33S R6W S8 BT.
- A Laurel 14" dia., bears S.25°E., 22 lks. dist. mkd. T33S R6W S17 BT.
- A Laurel 12" dia., bears S.78°W., 56 lks. dist. mkd. T33S R6W S18 BT.
- A Fir 20" dia., bears N.52°W., 29 lks. dist. mkd. T33S R6W S7 BT.

Douglas Co. Surveyors Office - James W. Byron and crew - July 2, 1963 - C.S. File 53/8-2

-----  
Found - Orig. 20" now 34" Fir snag, N.52°W., 18.1 ft., no scribing.  
Orig. 20" now 30" Fir snag, N.46°E., 14.5 ft., shows old axe marks.  
Orig. 14" now 16" Laurel snag, shows old rotted fce and axe work. No scribing found.  
Stump hole for orig. SW bearing tree.

This is in old burn area. The Firs were probably bark scribed. Ring count checks for size and all check record bearing and distance.

Set Brass cap at cor. mkd: County Surveyors Office

T 33 S R 6 W  
S 7 | S 8  
S18 | S17  
1963

- New BTs -6" Chinquapin bears S.7°E., 7.9 ft. scribed S17 T33S R6W CS BT.
- 11" Laurel bears S.75°W., 35.2 ft. scribed S18 T33S R6W CS BT.
- 3" Fir bears N.70°W., 20.0 ft. scribed CS BT.
- 5" R.Fir bears N.29°E., 20.4 ft. scribed S8 CS BT.

1963 B.Cap, 3 orig. BTs and 4 County BTs, found OK in BLM survey by Virgil Stanger, Group #1052, survey in 1982 - (DCSO records, Vol. 46 Pages 17589-90)

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Kris DeGroot - For: Silver Butte Timber Co. - Nov. 2014 - M166-21

-----

Found - A 1¼" iron post by Byron in 1963 per C.S. 53/8, firmly set, projecting 12" above the ground, with a properly mkd. 2½" brass cap, from which:

Remains of the original BTs -

A 20" Rotted fir stump bears N.50½°E., 15.0 ft (N.50¾°E., 23.5 lks)

A 34"x15' Fir snag bears N.50°W., 19.4 ft with saw & axe mks (N.50°W., 29 lks)

BTs by DCSO in 1963 -

A 24" D.Fir saw stump bears N.28½°E., 20.7 ft., set 8" MAG-Nail in ctr (N.29°E., 20.4 ft)

A 12" Chinquapin bears S.6¾°E., 8.0 ft with healed blaze (S.7°E., 7.9 ft)

A 20" Madrone bears S.76½°W., 38.1 ft with partially healed blaze (S.75°W., 35.2 ft)

A 24" D.Fir bears N.69°W., 19.8 ft with healed blaze (N.70°W., 20.0 ft)

New BT - A 16" D.Fir bears N.87¼°E., 22.6 ft scribed "T33S R6W S8 BT"