

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9020-21)

-----  
Set a Cedar post 4 ft. long, 4" sq., 20" in the ground, mkd. 1/4 S on W. face, for the quarter sec. cor., from which  
A Fir 6" dia., bears S.30°E., 15 lks. dist. mkd. 1/4 S BT  
A Cedar 10" dia., bears N.75°W., 26 lks. mkd. 1/4 S BT.

BLM dependent resurvey by Joseph S. Gawron, Cadastral Surveyor, under Group #'s 350 and 526,, surveyed Sept. 1963/July 1964 - (DCSO records Vol. 33 Page(s) 13843-44)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked

1/4  
S 7 S 8  
T 33 S R 6 W  
1966

from which

A D.Fir 8" dia., bears S.75°E., 44 lks. dist., mkd. 1/4 S 8 BT.  
A D.Fir 6" dia., bears N.79°W., 10 lks. dist., mkd. 1/4 S 7 BT.

Fd. OK, by G. Nygren, March 1994, M 118-79