

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9023)

Set a Yew post, 4 ft. long, 4" sq., 20" in the ground, marked ¼ S on W. face, for the ¼ sec. cor., from which
A Laurel 12" dia., bears S.55°E., 12 lks. dist. mkd. ¼ S BT.
A Laurel 15" dia., bears N.80°W., 18 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: R. Olson and M. Pounds - July 28-29, 1964 - C.S. File 51/264

Orig. Yew post missing, from which a:
12" Laurel S.55°E., 12 lks., now root hole and stubs of burned out Madrone in place, sprouts around edge.
15" Laurel bears N.80°W., 18 lks., now 27", portion of ancient cruiser markings in cut out face, no scribes remaining.
Old line blazes N. and S., top ridge, course E. 7.00 chs. S., in place. Creek, course East, 4.00 chs. North, in place.
Set 1½" x 36" galv. I.P. with 3" brass cap mkd. "Ore.St.Bd. of Forestry ¼ S5 S6 1964 RS359", 30" in ground and from which:
27" Madrone, orig., bears N.80°W., 11.9 ft., rescribed ¼ S6 BT RS359.
10" Chinquapin bears S.21°E., 10.6 ft. scribed ¼ S5 BT.
56" Fir stump bears N.68°W., 32.2 ft. scribed RS359.
Set 4 x 4 x 62" white painted cedar post, 1.5 ft. NE of corner pipe.
Oregon St. Forestry Dept. metal location poster on above 56" Fir stump.

Cor. Fd. OK by R. Thompson, April 1984, RM 3-61

Cor. Fd. OK by G. Nygren, March 1994, M 118-79
Found OK by G. Nygren, Oct. 2001 - M139-9