

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9019)

Set a Fir post 4 ft. long, 4" sq., 18" in the ground, marked $\frac{1}{4}$ S on N. face, for the $\frac{1}{4}$ sec. cor., from which
A Fir 26" dia., bears N.5°E., 60 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 36" dia., bears S.85°W., 58 lks. dist. mkd. $\frac{1}{4}$ S BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Oct. 19, 1967 - C.S. File 54/53-30

Found - 36" D.Fir now 48", S.85°W., 38.3 ft., faint bark scribe " $\frac{1}{4}$ S BT".
26" D.Fir now stump, N.5°E., 39.6 ft., no marks visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 33 S R 6 W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{8}{17}$
1967

New BT - 10" Tan Oak N.48°W., 26.0 ft. mkd. $\frac{1}{4}$ S8 CS BT.
Reblazed and rescribed:
48" D.Fir S.85°W., 38.3 ft. mkd. $\frac{1}{4}$ S17 CS BT.

Fd. OK, by G. Nygren, March 1994, M 118-79