

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9022)

Set a Fir post, 4 ft. long, 4" sq., 20" in the ground, marked ¼ S on N. face, for the ¼ sec. cor., from which
A Fir 15" dia., bears North 26 lks. dist. mkd. ¼ S BT.
A Fir 60" dia., bears S.30°E., 13 lks. dist. mkd. ¼ S BT.

Not Fd by J. Powell, 10/1969 (added 3/28/2017) C.S. 54/53-39: Good E-W blazed line. 1 fir cut into with chain saw on south side, opened with axe on north side. No evidence of cor.

Survey by Gerald Nygren, L.S. #1035 - For: City of Glendale -March 1994 - C.S. File 63/134 and M 118-79

Set 5/8" Iron rod with yellow plastic cap mkd: "Nygren LS 1035".
BTs - D.Fir 8" dia., bears S.76°W., 24.4 ft. scribed ¼ S8 BT.
D.Fir 8" dia., bears S.67°E., 11.2 ft. scribed ¼ S8 BT.
D.Fir 7" dia., bears N.62°W., 32.2 ft. scribed ¼ S5 BT.
Madrone 12" dia., bears N.70°E., 28.6 ft. scribed ¼ S5 BT.