

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9010)

Set post cor. to secs. 4, 5, 8 and 9 on East slope, from which

- A Fir 12" dia., bears S.40°E., 40 lks.
- A Cedar 20" dia., bears N.8°E., 24 lks.
- A Cedar 12" dia., bears N.43°W., 14 lks.
- A Fir 10" dia., bears S.60°W., 98 lks.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 431 survey dated March 29 1882 (DCSO records Vol. 21 Page(s) 9015-16 and Pages 9021/22)

The corner is gone, established new post from witness trees, viz.,

A Cedar, 4 ft. long, 4" sq., 20" in the ground, mkd. T33S R6W S4 on NE. face; S9 on SE. face; S8 on SW. face; and S5 on NW. face, also 5 notches on South and 4 notches on East angles of same, from which

- A Cedar 24" dia., bears N.8°E., 24 lks. dist. mkd. T33S R6W S4 BT.
- A Fir 16" dia., bears S.40°E., 40 lks. dist. mkd. T33S R6W S9 BT.
- A Fir 16" dia., bears S.60°W., 98 lks. dist. mkd. T33S R6W S8 BT.
- A Cedar 14" dia., bears N.43°W., 14 lks. dist. mkd. T33S R6W S5 BT.

Survey by George J. Wenderoth, Deputy Co. Surveyor - May 1946 C.S. File 38/221

Found - Two orig. BTs, both dead.

Set 1¼" Iron pipe. Mark:

- 20" Cedar S.82°20'W., 16.0 ft.
- 29" Cedar S.1°35'W., 51.2 ft.
- 14" Cedar S.63°52'E., 35.9 ft.
- 30" Cedar N.19°56'E., 89.5 ft.

BLM dependent resurvey by Joseph S. Gawron under Group #'s 350 and 526 surveyed Sept. 1963/July 1964 (DCSO records Vol. 33 Page(s) 13856-57)

The Sec. cor., monumented with an iron pipe 1½" dia., firmly set, protruding 14" above the ground, from which the remains of the original bearing trees:

(Cont. Next Page)

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An Incense Cedar snag 26" dia., bears N.8°E., 24 lks. dist., with scribe marks 4 BT visible on partially healed and weathered blaze.

A sawed D.Fir stump 24" dia., bears S.40°E., 40 lks. dist., with scribe marks BT visible on exposed blaze.

A sawed D.Fir stump 18" dia., bears S.60°W., 98 lks. dist., with scribe marks BT visible on exposed blaze.

An Incense Cedar snag, 16" dia., bears N.23°W., 14 lks. dist., with no marks remaining. (Rec. N.43°W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked

T 33 S R 6 W
S 5 S 4
S 8 S 9
1963

from which

A Ponderosa Pine 8" dia., bears N.25°E., 50 lks. dist., mkd. T33S R6W S4 BT.

A D.Fir 6" dia., bears S.13°E., 31 lks. dist., mkd. T33S R6W S9 BT.

A P.Pine 8" dia., bears S.34°W., 29 lks. dist., mkd. T33S R6W S8 BT.

A D.Fir 6" dia., bears N.45°W., 24½ lks. dist., mkd. T33S R6W S5 BT.

Insert Iron pipe inside iron post.

Fd. OK, by G. Nygren, March 1994, M 118-79

Fd. OK, by R. Thompson, April 1984, RM 3-61

Fd. OK, Feb. 1996 by R. Brown - M123-41