

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors,
under Contract #54, dated Feb. 19, 1855 (DCSO records Vol.
21 Page(s) 9010)

Set sq. sec. post, from which
A Fir 11" dia., bears S.68½°W., 90 lks.
A Fir 13" dia., bears N.24½°E., 20 lks.

Survey by J. Elmer Nelson, Civil Engineer - For: First Addn.
to the Glendale A.F. & A.M. Cemetery - March 1923 - Plat Vol.
5 Page 53

Set for initial point of plat, a 2" x 36" galv. I.Pipe.

Survey by George J. Wenderoth, Deputy Co. Surveyor - May 1946
C.S. File 38/221

Found - 2" Iron pipe at SE Corner Cemetery. Could find no
trace of BTs.
Marked - 20" Fir S.72°04'W., 34.3 ft.
12" Alder S.42°05'E., 27.0ft.

Survey by George J. Wenderoth - For: O. Miller and L. Coate
-Dec. 31, 1962 - C.S. File 52/137 and M 24-44

Found - 2" I.P. and remains of old bearing trees.
Scribed -18" Fir S.41°04'E., 29.8 ft.
12" Alder S.32°20'W., 35.5 ft.

Fd. OK, DCSO, Oct. 1967 C.S. File 54/53-25
Fd. OK, by Max Hull, Jan. 1984, M 96-75
Fd. OK, April 1984, RM 3-61
Fd. OK, Feb. 1996 by R.Brown - M123-41

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- Oct. 10, 2006 - C.S. File 67/14-31

Found - 2" ID Iron pipe 4" below ground w/3 ft. tall steel
fence post 0.5 ft. East. 1923
1" I.D. iron pipe projects 2" above ground bears
N.1°W., 3.05 ft. No previous rec. fd.
18" now 37" dia., D.Fir fully healed double blaze
visible bears S.46°E., 29.8 ft. (rec. S.41°04'E.,
29.8 ft.) 1962 BT
20" Fir now very rotted 1 ft. tall stump bears
S.72°W., 34.3 ft. (agrees w/rec.) 1946 BT

continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

No trace of any other accessories fd.
New - 14" dia., W.Fir double blazed & scribed "¼ S5 CS BT"
bears S.24½°W., 39.7 ft.
31" dia., D.Fir double blazed & scribed "¼ S4 CS BT"
bears N.46°E., 45.0 ft.
Triple trunk maple, southerly trunk is 8" dia., & is
scribed "¼ S5 CS BT" bears N.9½°W., 28.3 ft.
SE corner of cemetery fence (4 ft. tall chain link)
bears N.75°W., 12.0 ft.
Note - Lies near SE corner of cemetery.
Compass decl. 16½°E.