

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 4 and 5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8638)

-----  
Set post, cor. to secs. 4 and 5, T33S R6W, from which  
A Vine Maple 5" dia., S.33°W., 19 lks. dist.  
A Red Fir 7" dia., S.19°E., 36 lks. dist.

H.L. Eppstein - Wit: J.H. Wolford - June 12, 1929 - C.S. File 14/1

-----  
A wagon skein in place for corner set by J. Elmer Nelson from old stake. Set new witness trees:  
30" Maple S.7½°W., 94 lks.  
24" Fir S.75¼°W., 128 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Oct. 2, 1967 - C.S. File 54/53-11

-----  
Found - Wagon skein at section corner.  
30" now 39" Maple S.7½°W., 62.0 ft., shows scar.  
No trace of SW tree, falls in street.  
New BT - 14" Maple S.83°W., 51.2 ft. mkd. T33S R6W S5 CSBT  
This corner lies 198.0 ft. East of corner to secs. 32 and 33 only, T32S R6W, approx. 25 ft. East of Third Street.

Fd. OK, Greg Lang, Feb. 1990, M 110-6