

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1736, surveyed June/Sept. 1994 - (DCSO records Vol. 52 Page(s) 19732-3)

-----  
Point for the center ¼ sec. cor. of sec. 9, at intersection with the E. and W. centerline.  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T33S R6W  
C ¼ S 9  
1994

from which

A fir, 12" dia., bears N. 88¼° E., 39½ lks. mkd. C¼ S9 BT.

A fir, 12" dia., bears N. 27° W., 13 lks., mkd. C¼ S9 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established by person(s) unknown, bears S. 0° 02' 00" E., 1.790 chs. dist., monumented with an iron pipe, 3/4 in. diam., with a 1 in. diam. pipe fitting on top, projecting 6 ins. above the ground.

Fd. BLM BC by H. Farber, 6/2017 - M173-44

Russell Badgley - For: Weyerhaeuser Co. - 8/2020 - M178-8

-----  
Found - A 2½" USBLM stainless steel post by Simon in 1994 per Group #1736, firmly set and projecting 2" above the ground, with a 3 1/4" brass cap properly marked per the record: from which

A 12" D.Fir bears N.88°45'E., 26.2 ft w/partially healed double blaze (N.88¼°E., 39½ lks) 1994

A 16" D.Fir bears N.26°15'W., 8.4 ft w/partially healed double blaze (N.27°W., 13 lks) 1994

New RMs- A 5/8"x30" iron rod with 2" BTS alum. cap stamped "RM 1 2020" bears S.67°33'18"E., 25.99 ft.

A 5/8" x 30" IRON ROD WITH 2" BTS alum. cap stamped "RM 2 2020" bears S.55°55'16"W., 15.47 ft.

NAD83(2011) LAT: 42°43'04.06770"N LONG: 123°24'57.67831"W