

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9010)

Set qr. sec. post, from which  
A Laurel 10" dia., bears S.30°E., 35 lks.  
A Sugar Pine 15" dia., bears N.54°E., 33 lks.

Survey by George J. Wenderoth - For: O. Miller and L Coate - Dec. 31, 1962 - C.S. File 52/137 and M 24-44

Found - 56" Pine N.54°E., 21.8 ft., only stump remains.  
Iron rod with pulley on top, 5 ft. North of bearing and distance.

Set 1" I.Pipe at corner.  
Scribed -7" Chinquapin N.2°05'E., 33.7 ft.  
5" Madrona N.64°43'E., 32.0 ft.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1736, surveyed June/Sept. 1994 - (DCSO records Vol. 52 Page(s) 19733)

The ¼ sec. cor. of secs. 4 & 9, perpetuated by Wenderoth, in 1962, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 7 ins. above the ground, from which the remains of an original BT:

A pine stump, 36" dia., bears N.54°E., 33 lks., no marks visible on burned out blaze.

and bearing trees mkd. by Wenderoth

A chinquapin, 14" dia., bears N.0¾°E., 51 lks., with illegible scribe marks visible on a partially healed blaze.

A madrone, 11 ins. diam., bears S.66¼°E., 47 lks., with illegible scribe marks visible on a partially healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd.

T33S R6W

¼ S 4  
S 9

1994

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, an iron rod, 3/4 in. diam., with a pulley on top, established by person(s) unknown & recorded by Wenderoth, bears N. 0¾° E., 0.09 chs. dist.

cont.

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Russell Badgley - For: Weyerhaeuser Co. - 8/2020 - M178-8  
-----

Found - A 2½" USBLM stainless steel post by Simon in 1994 per Group #1736, firmly set and projecting 4" above the ground, with a ¾" brass cap properly marked per the record: from which

A 36" Pine stump bears N.50°30'E., 22.0 ft w/burned blaze (N.54°E., 21.8') 1962 (N.54°E., 33 lks) OBT & BLM 1994

A 16" Chinquapin N.01°00'E, 33.3 ft w/healed blaze (N.2°05'E., 33.7') 1962 (North 33.5') 1973 (N.0¾°E., 51 lks) 1994

A 11" madrone bears S.66°15'E., 31.4 w/part. healed blaze (S.64°43'E., 32.0') 1962 (S.64°E., 32.0') 1973 (S.66¼°E., 47 lks) 1994

New BT - A 17" D.Fir bears N.85°15'W., 14.2 ft scribed "¼ S4 BT" on dbl blaze

Note - The ¾" iron rod with pulley on top bears N.2°11'13"E., 5.91 ft (N.0¼°E., 0.09 chs) 1994

NAD83(2011) LAT: 42°43'30.03292"N LONG: 123°24'57.69718"W