

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION WC No. 1/4 Cor. for Sec. 4 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8637)

-----  
Set ¼ sec. post, from which  
    An Ash 12" dia., bears S.49°E., 15 lks. dist.  
    An Ash 14" dia., bears S.34°W., 78 lks. dist.

H.L. Eppstein; J.H. Wolford - June 12, 1929 - C.S. File 14/1

-----  
I set corner from old stake in place. Set 1" x 48" Iron pipe. Marked new witness trees:  
    14" Ash S.64°W., 98 lks.  
    12" Maple N.81°W., 82 lks.

B. B. Irving - Jim Byron, Ray Irving - Dec. 17, 1953 - C.S. File 45/232

-----  
Found - 3/4" I. pipe. Corner identified from I.P. and old BTs. Scribe marks on said trees visible.  
Blazed and scribed:  
    12" Maple S.21°E., 27.1 ft. mkd. ¼ S CS BT.  
    16" Alder S.64°E., 43.0 ft. mkd. ¼ S CS BT.

Geo. J. Wenderoth - Dec. 21, 1962 - C.S. File 52/137 and M 24-44

-----  
(Corner washed away)  
Found - The 12" Maple S.21°E., 27.1 ft. for the ¼ cor., the only tree left.  
Set 1" I.Pipe, 38.8 ft. West on Tsp. line, scribed:  
    26" Maple S.35°04'W., 33.1 ft.  
    12" Maple S.32°45'E., 31.6 ft.  
Set 1" I.Pipe 76.8 ft. South on centerline of section 4, scribed:  
    36" Maple S.24°06'E., 76.5 ft.  
    36" Cedar S.58°05'W., 84.8 ft.

Fd. OK, DCSO, John Powell, Oct. 3, 1967, C.S. File 54/53-21

1" I.P. 76.8 ft. South on centerline, Fd. OK, M. Armstrong, April 1986, M 101-4

Douglas County Surveyors Office - Randall Smith and Stephen J. Flause, crew - May 23, 1986 - C.S. File 62/34-8

-----  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION WC No. 1/4 Cor. Sec. 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 1" I.P. flush with ground, set by Wenderoth as South Wit. Cor. No other monuments found. The ¼ cor. and West wit. corners set by Wenderoth have been washed away by Cow Creek.

No original BTs or BTs per 1953 found.

14" now 29" dia. Ash with double rotted out blaze facing ¼ cor. position. (1929) BT is also SW BT to West wit. cor., wrongly identified as a Maple, with a double partially healed blaze, scribing visible, facing position of Wenderoth West wit. corner.

NW BT per 1929 is gone.

SE BT to West wit. cor. per 1962, down and washed out of position.

Found BTs to South wit. cor.:

36" now 43" dia. Maple with a fully healed single blaze bears S.24°06'E., 78.0 ft. (Rec. S.24°06'E., 76.5 ft. to face)

36" now 36" dia. I.Cedar with a fully healed single blaze bears S.58°05'W., 86.2 ft. (Rec. S.58°05'W., 84.4 ft. to face)

Computed No. ¼ cor. Sec. 4, T33S R6W, as perpetuated by Eppstein and Wenderoth as evidenced by South Wit. Cor., an Ash (SW BT, per Eppstein), distance to Ash appears to be face measurement. New West wit. cor. placed on a line between So. ¼ S33 T32S R6W and computed position of N. ¼ S4 T33S R6W.

A DCSO brass cap protrudes 4" above ground. Cap stamped. Douglas County Surveyor

T33S  
East  
W.C. to Cor  
1/4 S4 70.0 ft.  
only  
R6W  
1986

The computed position for No. ¼ S4 bears East, 70.0 ft.

New Accessories:

29" Ash previously scribed by Eppstein and Wenderoth bears S.21 3/4°E., 29.9 ft.

So. ¼ Cor. S33, T32-6, DCSO BC/IP bears West, 149.2 ft.

So. Wit. Cor., 1" I.P., bears S.42½°E., 103.8 ft.

Sketch of area on notes in C.S. File. See DCSO monument recovery quad books for coordinate information.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION WC No. 1/4 Cor. Sec. 4 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Randall W. Smith; Stephen J. Flause, deputies - April 6, 1988 - C.S. File 62/52-14

Found - 1" I.D. x 32" long iron pipe with a 1986 DCSO brass cap, bent and laying horizontal on top of ground, out of position, set as West witness corner. BC/IP pulled out of ground by recent cat work.  
1" I.P. flush with ground set by Wenderoth as South witness corner.

BTs and BOs to West witness corner:

14" now 29" dia. Ash with a double rotted out blaze facing  $\frac{1}{4}$  position as per Eppstein, tree also is SW BT to West wit. cor., wrongly identified as a Maple, with a double partially healed blaze, scribing visible facing position of Wenderoth West wit. cor. BT bears S.21  $\frac{3}{4}$ °E., 29.9 ft. from position of West wit. cor. as established in 1986.

South  $\frac{1}{4}$  cor. for Sec. 33, T32S R6W, DCSO BC/IP, bears West, 149.2 ft.

5/8" Iron rod (East wit. cor. to S.  $\frac{1}{4}$  cor. S33 T32-R6W) wrongly noted on sketch in C.S. 62/34 as a 1" I.P., bears West 109.2 ft.

South Wit. Cor., a 1" I.P. set flush with ground, bears S.42 $\frac{1}{2}$ °E., 103.8 ft. (Wenderoth)

BTs to South Wit. corner per Wenderoth, are alive and in good shape.

Set West Wit. cor. established in 1986, is reestablished from found accessories per 1986. 1986 DCSO BC/IP is straightened and reset. DCSO BC/IP protrudes 6" above ground and is surrounded by an 18" dia., 6" high mound of stone. A white steel guard post is set 1' East of West wit. corner. "RESET 1988" is added to brass cap.

New Accessory:

1" I.D. Iron pipe, (4" below ground w/3/4" I.D., protrudes 14" & bent to ground, 3/4" I.P. along N. edge of 1" I.P), bears W., 40.2 ft. (Source unknown)

Gerald Nygren - 11/23/94 - M 121-31

Found two witness monuments -

1" dia. I.P. w/BC which bears, S.89°26'45"W., 70 ft.

1" dia. I.P., bent which bears, S.00°03'28"E.. 76.8 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/18/2000 - C.S. File 66/16-23

West WC to N  $\frac{1}{4}$  cor. & Ash BT now gone.

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION WC No. 1/4 Cor. for Sec. 4 only

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Found OK by R. Wytcherley, July 2001 - M137-18 & CS65/38-3C

FD. WC by R. Wytcherly July 2006 - M151-33