

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 400520

PRIMARY CORNER DESCRIPTION S. 1/16 cor. betw. secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Milner L. Larson - For: Robert Dollar Co. - August 1965 - M 30-50

Set 7/8" Iron bolt - S 1/16
10" Yew S.33°51'W., 25.8 ft.
8" D.Fir S.22°59'E., 57.8 ft.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1736, surveyed June/Sept. 1994 - (DCSO records Vol. 52 Page(s) 19726-7)

The S 1/16 sec. cor. of secs. 9 & 10, established by Larson, in 1965, recorded in survey No. 223-65, & is accepted as the corner; monumented with an iron bolt, 7/8 in. diam., firmly set, projecting 20 ins. above the ground, from which bearing trees mkd. by Larson:

A fir, 19" diam., bears S.22¼°E., 88 lks. dist., with healed blaze.

A yew, 13" diam., bears S.35°W., 39 lks. dist., with scribe marks RE 3642 BT visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron bolt, with brass cap mkd.

S 1/16
S 9 | S 10
1994

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. BLM BC by H. Farber, 6/2017 - M173-44

Fd. BLM BC & accessories by R. Badgley, 8/2020 - M178-8

NAD83(2011) LAT: 42°42'50.30180N LONG: 123°24'22.67260"W