

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias	Description

GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9008)

Set qr. sec. post, from which
A Maple 3" dia., bears S.47°W., 46 lks.
A Maple 4" dia., bears S.54°E., 49 lks.


Survey by Milner L. Larson - For: Robert Dollar Co. - August 1965 - M 30-50

Set 7/8" Iron bolt - W ¼.
12" D.Fir S.85°17'W., 117.5 ft.
26" I.Cedar N.2°18'E., 57.9 ft.

Fd. OK, - DCSO - Oct. 1967 C.S. File 54/53-17

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1736, surveyed June/Sept. 1994 - (DCSO records Vol. 52 Page(s) 19727)

The 1/4 sec. cor. of secs. 9 & 10, reestablished at proportionate measurement by Larson, in 1965. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an iron bolt, 7/8 in. diam., firmly set, projecting 16 ins. above the ground, from which bearing trees mkd. by Larson:
A cedar, 35" diam., bears N.2¼°E., 92½ lks. dist., with healed blaze.
A fir, 25" diam., bears S.86¼°W., 178 lks. dist., with healed blaze.
At the corner point
Set a stainless steel post, 28 ins. long, 2 ½ ins. diam., 22 ins. in the ground, directly over the iron bolt, with brass cap mkd.



Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Ok by R. Wytcherley - 10/2010 - M161-44
Fd. BLM BC by H. Farber, 6/2017 - M173-44

continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23790)

The ¼ sec. cor. of secs. 9 & 10, reported by Simon in 1994, monumented with a stainless steel post, 2½" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd from which bearing trees reported by Simon

A cedar, 43" dia., bears N.2¼°E., 61.1 ft., with a healed blaze.

A fir, 33" dia., bears S.86°W., 117.5 ft., with a healed blaze.

Fd. BLM BC & accessories by R. Badgley, 8/2020 - M178-8
NAD83(2011) LAT: 42°43'03.54624N LONG: 123°24'22.52335"W