

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 400560

PRIMARY CORNER DESCRIPTION N. 1/16 cor. betw. secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Milner L. Larson - For: Robert Dollar Co. - August 1965 - M 30-50

Set 1½" Iron pipe - N 1/16
8" D.Fir N.22°50'E., 53.2 ft.
15" D.Fir N.27°10'W., 67.4 ft.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1736, surveyed June/Sept. 1994 - (DCSO records Vol. 52 Page(s) 19727-8)

The N 1/16 sec. cor. of secs. 9 & 10, established by Larson, in 1965, & is accepted as the corner; monumented with an iron rod, 1½ ins. diam., firmly set, projecting 8 ins. above the ground, from which bearing trees mkd. by Larson:

- A fir, 18" diam., bears N.43°E., 53 lks. dist., with healed blaze.
- A fir, 27" diam., bears N.27°W., 103 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

N 1/16
S 9 | S 10
1994

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. From this point, an iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above the ground, established by person(s) unknown and recorded by Larson in 1965, bears North, 0.348 chs. dist.

Fd. Ok by R. Wytcherley - 10/2010 - M161-44