

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8637)

Set post, cor. to secs. 3 and 4, T33S R6W, from which
A W.Fir 30" dia., bears S.47°E., 55 lks. dist.
A W.Fir 30" dia., bears S.45°W., 82 lks. dist.

Cor. Fd. and used in survey for H.E. Cliff, Nov. 20, 1873, Field Book 97 Page 30

Survey by Ronald A. Brandt - For: Robert Dollar Co. - May 1973 - C.S. File 55/294 and M 49-21

Set 1" x 60" I.Rod, 12" deep, from which bears
1" x 36" I.Rod 4" high, N.61°32'27"W., 22.96 ft. at South side of small cherry tree.
1" x 36" I.Rod 4" high, N.44°15'33"E., 56.26 ft. at South side of a cedar fence post.
1" I.Pipe, 15" deep, N.89°30'59"W., 209.68 ft. set by Nelson, 1933.

Gerald Nygren - 11/23/94 - M 121-31

Monument FD. -
1" I.R., 20" deep in field NE of Sethers barn said 1" I.R., bears N.05°12'07"W., 1.45' from computer cor. position.

Raymond Wytcherley - For: Misty Morningstar - 7/2001 - C.S. File 65/38-3E - M 137-18

Set - 5/8" I.Rod W/Yel. plastic cap 8" below surface, from which existing steel fence posts, measured to center of base of posts, on which I set BT signs:
A steel fence post bears S.8°52'W., 132.4 ft.
A steel fence post bears N.65°36'E., 81.2 ft.
A steel fence post bears N.3°12'W., 29.6 ft.
A 1" I.Rod per Brandt bears N.0°32'W., 1.45 ft.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21448)

The ¼ sec. cor. of sec. 34 only, the standard sec. cor. of secs. 3 and 4, on the N. bdy. of T33S R6W reestablished by proportionate measurement, by Wytcherley, in 2001, bears N.89°44'50"W., 2453.28 ft., continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, buried 7" below the ground, with plastic yellow cap mkd. WYTCHERLEY LS 2724, from which accessories reported by Wytcherley

A "T" iron fence post, bears N.65½°E., 81.2 ft.

A "T" iron fence post, bears S.8¾°W., 132.2 ft.

A "T" iron fence post, bears N.3¼°W., 29.6 ft.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 43" in the ground, top 15" below surface, directly over the iron rod, with brass cap mkd.

S 4 | S 3
T33S R6W
SC
2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From the standard sec. cor. of secs. 3 & 4, T33S R6W a point established as this same cor. by Brandt, in 1973, bears N.1°31'W., 1.40 ft., monumented with an iron rod, 1" dia., buried 12" below the ground, and was not used for control in this survey.