

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Not in Douglas County</p>
<p>GLO survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9007)</p> <p>-----</p> <p>Set qr. sec. post, from which A Dogwood 3" dia., bears S.12°W., 18 lks. A Dogwood 3" dia., bears N.25°W., 45 lks.</p>
<p>Survey by Donald R. Martin - For: Herbert Lumber Co. - Wit: E.N. White and Milt Hammersley - July 1960 - C.S. File 51/118</p> <p>-----</p> <p>No original BTs. Found Original 2 x 2 Post. I scribed 15" B.Oak S.4°E., 42 ft.</p>
<p>BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23783)</p> <p>-----</p> <p>The ¼ sec cor of secs 10 & 15, reestablished by proportionate measurement by Hull, in 1993. There is no remaining evidence of the original cor., therefore this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 1" above the ground, with yellow plastic cap mkd. HULL RS 901, from which bearing trees mkd. by Hull</p> <ul style="list-style-type: none">A white oak, 9" dia., bears N.88¾°E., 65.0 ft., with a healed double blaze.A white oak, 6" dia., bears S.24¼°E., 30.5 ft., with a healed double blaze.A white oak, 14" dia., bears N.70°W., 46.6 ft., with a healed double blaze.A live oak, 14" dia., bears N.39½°W., 40.6 ft., with scribe marks S ¼ RS 901 BT visible on partially healed blaze. <p>At the corner point Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T33S R6W ¼ $\frac{S\ 10}{S\ 15}$ 2018</p>
<p>See Josephine County Surveyor's Office for the most current information</p>