

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wells Lake and Geo. W. Hyde, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 21 Page(s) 9008-9)

-----  
Set ¼ sec. post, from which  
    B.oak 10", bears N.16°E., 59 lks.  
    Laurel 5", bears S.8°W., 53 lks.

Not Fd. DCSO, Oct. 1967 (added 3/27/2017), C.S. File 54/53-17  
Fd squared stake, where trees were is logged & cat trail

Gerald Nygren - 11/23/94 - M 121 -31

-----  
Set - 5/8" I.R. 30" long extended 2" above ground w/cap mkd:  
    "NYGREN LS 1035"  
    6" Tan Oak, S.10°W., 6.1', scribed "X BT"  
    5" Madrone, S.84°W., 6.4', scribed "X BT"  
    5" Tan Oak, N.70°E., 35.9', scribed "X BT"  
    15" Madrone, N.36°W. 8.2', bark scribed "¼ S10 BT"

Fd. IR & 4 BTs Set a 6 ft. steel post 2 ft. north by D  
Edwards, 2/2016 - M170-55A&B

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23788-9)

-----  
The ¼ sec cor of secs. 3 & 10, reestablished by proportionate measurement by Nygren, in 1995. There is no remaining evidence of the original cor., therefore this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 3" above the ground, with yellow plastic cap mkd. NYGREN LS 1035, from which bearing trees mkd. by Nygren

    A tan oak, 6" dia., bears N.70¼°E., 35.5 ft., with scribe marks X at breast height and BT at the base visible on bark.

    A tan oak, 8" dia., bears S.12¼°W., 6.0 ft., with scribe marks X at breast height and BT at the base visible on bark.

    A madrone, 6" dia., bears S.78½°W., 6.3 ft., with scribe marks X at breast height and BT at the base visible on bark.

    A madrone, 15" dia., bears N.35¾°W., 8.6 ft., with scribe marks ¼ S3 BT visible on bark.

At the corner point

continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.

T33S R6W

¼  $\frac{S\ 3}{S10}$

2018

Fd. as per record. by P Drossos 1/2024 M183-37