

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 537700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 35 only, T32-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A D.Fir, 14" dia., bears N.35 $\frac{3}{4}$ °W., 57.2 ft., with scribe marks S $\frac{1}{4}$ S35 BT visible on open blaze.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., directly over the iron rod, 24" in the ground, with brass cap mkd.

T32S R6W

$\frac{1}{4}$ S 35

T33S R6W

2006

The geographic position (NAD 1983(CORS96)) of the $\frac{1}{4}$ section corner of section 35 only, on the south boundary of the township, as determined by a conventional tie to a temporary point, established utilizing NAVSTAR GPS static data and NGS Online Positioning User Service (OPUS) with NSRS CORS stations, "CAPE MENDOCINO 1", "KLAMATH FALLS 1", and "APPLETON", is as follows:

Latitude: 42°44'22.32"N. Longitude: 123°22'38.12"W.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, a point established as the $\frac{1}{4}$ sec. cor. of sec.35 by Thompson, in 1971, bears N.27°05'W., 9.5 ft. monumented with an iron pipe, 2" dia., firmly set, projecting 15" above the ground, and was not used for control in this survey, from which bearing trees mkd. by Thompson

A D.Fir, 20" dia., bears N.75 $\frac{1}{2}$ °E., 51.6 ft., with a healed upper and lower blazes.

A sawed D.Fir stump, 20" dia., bears S.10°W., 40.0 ft., with a partially healed blaze.

Also from the $\frac{1}{4}$ sec. cor. of sec. 35 only, the standard $\frac{1}{4}$ sec. cor. of sec. 2, on the N. bdy. of T33S R6W bears S.89°44'05"E., 198.65 ft.